

# CNM-MSL-550S

## SKID STEER LOADER



### PRODUCT INFORMATION

Certification:



Engine Model	Cummins
Rated power	36.8KW
Cylinder	4
Intake method	Naturally aspirated
Emission standard	National III
Rated load	890Kg
Overturning load	≥ 1780
Maximum digging force	≥ 25KN
Bucket capacity	0.4m <sup>3</sup>
Travel speed	0-12km/h
Hydraulic flow	55L/Min
Hydraulic pressure	21Mpa
Fuel tank capacity	80L
Operation quality	2880±3%
Tire model	10-10.5

Maximum operating height	3790mm
Height to bucket pin	3020mm
Cab roof height	2095±5%mm
Horizontal length of bucket on the ground	3450±5%mm
Bucket pin horizontal length	2700±5%mm
Max horizontal distance of bucket bottom	2846±5%mm
Maximum unloading height	2384±5%mm
Unloading distance	520±1%mm
Flip angle of bucket on the ground	27±2mm
Flip angle of bucket at the highest position	43±2mm
Wheel width	1370mm
Ground clearance	185±2%mm
Tail length	1160±5%mm
Vehicle width	1640±2%mm
Bucket width	1800±2%mm

### 产品细节

**1**  Yanmar 380 three-cylinder water-cooled engine, powerful

**3**  Standard cab, safer and more reliable, dustproof and noise-proof

**5**  With rearview mirror, safe operation, safer construction

**2**  Minimalist central control, easy to use and operate

**4**  Hydraulic pilot operation, more flexible and smooth operation

**6**  Thickened bulldozer can be adjusted up and down







