

SYL0080DJ1






Unit Parameters

Model	SYL0080DJ1
Frequency (Hz)	50
ESP (kW/kVA)	85/106
Rated Power (kW/kVA)	77/96
Rated Voltage (V)	400
Phase	3
Speed Control Type	Electronic speed control



Unit Size and Weight

Length (mm)	3440
Width (mm)	1140
Height (mm)	2000
Net Weight (kg)	2250

☐

☒

☐


* The above is for reference only, the actual size and weight are subject to the final design drawings.

SYL0080DJ1



Engine

Brand		HUNAN DEUTZ
Model		BF4M1013EC G1
No. of Cylinders		4
Displacement (L)		4.76
Bore × Stroke (mm)		108×130
Starter Voltage (V)		24
Fuel Consumption (L/h)	100% load	24.2
	75% load	18.0
	50% load	12.2
	25% load	6.7



Alternator

Brand		Leroy Somer
Model		TAL A44D
Mode of connection		Three phases and four lines
Connection type		Y-shaped connection
Exciter system		SHUNT
Voltage regulator		R120
Bracket type		Single bearing



Controller

Brand		DEIF
Model		SGC420MKII

Generator



SYL0080DJ1



Configurations

“☒” configuration items

“☐” No configuration items

Standard configuration	Optional configuration	
☒ Engine	☒ Fuel-water separator	☐ Pre-lubrication system
	☐ Water jacket heater	☐ Inlet air shutdown valve
	☐ Engine oil heater	☐ Gas start system
	☐ Heavy-duty air cleaner	
☒ Alternator	☐ Permanent magnet generator	☐ Stator temperature sensor
	☐ Digital voltage regulator	☐ Bearing temperature sensor
	☐ Anti-condensation heater	☐ Differential protection
☒ Single-machine control	☐ Parallel control	☐ Redundancy control
	☐ Grid-connected control	☐ Remote monitoring system
☐ 40℃ Radiator	☒ 50℃ Radiator	
☒ Unit integrated output	☐ Individual output cabinet	
☒ Battery negative switch	☐ Battery charger	
☒ Maintenance-free lead-acid battery and cable		
☒ Industrial muffler	☐ Residential muffler	☐ Fire extinguishing muffler
☐ No fuel tank	☒ Chassis tank	☐ Daily-use fuel tank
☒ Rubber damper	☐ Spring bumper	
☒ Steel chassis	☒ Silent box type noise reduction box	☐ Container type noise reduction box
	☐ Tool kit	

*Special instructions:

The Rated power is the maximum power that a unit can operate continuously with variable load under standard environmental conditions, and is allowed to operate at an overload of 10% for 1 hour every 12 hours.

ESP refers to the maximum power that a generator set can operate continuously at variable loads under standard working conditions. The power of the generator set has been adjusted to its maximum, therefore overloading operation is not allowed.

*Operating conditions and power correction:

Altitude: ≤ 1000m (power correction required when >1000m).

Environmental temperature: 40 ℃ (Rated power correction required when >40 ℃, ESP power correction required when >25 ℃).

Relative humidity: ≤ 60%.

Land use.

Fixed on the ground during power supply to prevent movement.

When the operating conditions of the generator set do not meet the above conditions, the generator set needs to meet user needs through optional configurations, and the rated power value of the generator set needs to be corrected under high altitude and high temperature conditions.