

HERCULES

4KG 6KG 9KG 12KG

Dry Chemical Powder Fire Extinguisher



Information

Dry chemical powder fire extinguishers are the most cost effective solution for fighting fires. They are capable of fighting most common classes of fire including, Class A, Class B, Gas and Electric fires.

The silicon monoammonium phosphate dry powder melts upon contact with hot surfaces. This forms a barrier that between the fuel and oxygen and kills the fire.

On a per kilo basis, dry powder is the most effective against Class A and B fires, making it suitable for vehicle fires.

Compliance



EN3



SG Fire Code



CE



Germany

Fully compliant to Singapore Fire Code and SCDF requirements. Comes with Certificate of Compliance and serial numbered labels for fire certificate.

Meticulously tested in both Singapore and Germany.

Fire Class



Class A



Class B



Gas



Electric

Under SCDF regulations, Singapore fire extinguishers cannot have Gas or Electric icons. SCDF recommends that the energy source be switched off before fire fighting.

Accessories



L Bracket (4KG) P/N: FEL-K-BRK02
L Bracket 6/9/12 P/N: FEL-K-BRK04



Default option is the L bracket



Plastic Base (Optional)
Plastic base (4KG) P/N: FEA-K-BA04
Plastic base (9KG) P/N: FEA-K-BA09

SPECIFICATIONS

Model	FT01-04A-00	FT01-06A-00	FT01-09A-00	FT01-12A-00
Capacity	4KG	6KG	9KG	12KG
Propellant	Nitrogen, Stored Pressure			
Test Standard	SS EN3, BS EN3			
Discharge Distance	> Est. 3.5M	> Est. 4M	> Est. 5M	> Est. 5M
Discharge Time	12 Sec	12 Sec	14 Sec	31 Sec
Body Diameter	138 MM	160 MM	185 MM	190 MM
Total Height	447 MM	520 MM	540 MM	590 MM
Total Weight	6.6 KG	9.4 KG	13.4 KG	16.6 KG
Operating Temperature	-20°C to 60°C			
Pressure	15 Bar Working Pressure / 30 Bar Test Pressure			
Fire Rating	27A : 113B	34A : 183B	43A : 183B	55A : 233B
Pack Dimension(mm)	155x290x470 (2 per box)	165x175x535 (1 per box)	195x195x555 (1 per box)	200x200x610 (1 per box)
PART NO	FEL-FT-D04	FEL-FT-D06	FEL-FT-D09	FEL-FT-D12