

# S450 Specs & Compare

## ▲ S450 Key Specifications

### S450

Horsepower

**36.5 kw**

Rated Operating Capacity (ISO)

**621 kg**

Operating Weight

**2436 kg**

Auxiliary Std Flow

**63.2 l/min**

Joystick Control

**Optional**

## ▼ Engine

### S450

Horsepower

**36.5 kw**

## ▼ Performance

### S450

Rated Operating Capacity (ISO)

**621 kg**

Tipping Load

**1243 kg**

Operating Weight

**2436 kg**

Travel Speed

**12.3 kmh**

Travel Speed (2-speed option)

**14.8 kmh**

### ▼ Capacities

**S450**

Fuel Tank

**53.8 l**

### ▼ Hydraulic System

**S450**

System Relief @ Quick Couplers

**22800 kPa**

Auxiliary Std Flow

**63.2 l/min**

### ▼ Dimensions

**S450**

Length without Attachment

**2499 mm**

Length with Standard Bucket

**3173 mm**

Width

**1488 mm**

Width (with bucket)

**1575 mm**

Height with Operator Cab

**1976 mm**

Height to Bucket Hinge Pin

**2781 mm**

Reach @ Maximum Height

**528 mm**

Turning Radius

**1941 mm**

Wheelbase

**899 mm**

▼ **Features**

**S450**

Joystick Control

**Optional**

Air Conditioning

**Optional**

Adjustable Seat

**Standard**

Backup Alarm

**Standard**

BICS System (Interlock)

**Standard**

Cab Enclosure

**Optional**

Sound Option

**Optional**

Cab Heater

**Optional**

Operating Lights

**Standard**

Parking Brake

**Standard**

Radio

**Optional**

Rear Window

**Standard**

Top Window

**Standard**

Lift-Arm Support

**Standard**

Seat Belt

**Standard**

Suspension Seat

**Optional**

Two Speed Travel

**Optional**

Deluxe Instrumentation

**Optional**

Engine Shutdown

**Standard**

Hydraulic Bucket Positioning

**Optional**

High Flow Option

**Not Applicable**

Auxiliary Hydraulics

**Standard**

Spark Arrestor Muffler

**Standard**

Bob-Tach Attachment System

**Standard**

Power Bob-Tach

**Optional**

ACS (Switchable Controls)

**Not Applicable**

Ride Control

**Optional**

Rear Hydraulics

**Optional**

Horn

**Standard**