

SDG220S-3A7

Specification

GENERATOR

Type	Dual Voltage (Manual parallel)
Frequency (Hz)	50 / 60
3-phase 4 wires	
- Prime Output (kVA)	200 / 220
- Stanby Output (kVA)	220 / 242
- Voltage (V)	200/400 / 220/440
- Current (A)	577/289 / 577/289
Single-phase auxiliary output	
- Voltage (V)	100 / 110
- Dedicated terminals (kVA)	-
- Outlets (kVA)	1.5×4 / 1.65×4
Power factor (%)	3-phase 80 (lagging) / Single-phase 100

ENGINE

Make, Model	KOMATSU SAA6D125E-2-B
Type	Direct-Injection, Turbo-Charged, Intercooled
Rated output (kW)	178 / 204
Rated output (PS)	242 / 277
Rated speed (min-1)	1500 / 1800
Fuel tank capacity (L)	390
Engine oil amount (L)	42
Battery × quantity	170F51×2

DIMENSION & WEIGHT, etc

L×W×H (mm)	3700×1300×1750
Dry weight (kg)	3290
Operating weight (kg)	3700
Sound power level in decibels (dB)	93 / 95
Sound pressure level (dB[A])	64 / 65
Designated emissions regulation	JPN Stage 2

●Specifications are subject to change without notice.