

玻璃幕墙小型吸吊设备 HP-GI

Glass curtain wall small-scale suction crane equipment HP-GI

- 设备小巧轻便操作简单，自重仅55KG携带方便，最大载重500KG，可翻转可旋转
The equipment is small, light and easy to operate. Its weight is only 55KG and it is easy to carry. The maximum load is 500KG. It can be turned and rotated.
- HP-GI系列设备广泛应用于玻璃搬运及玻璃幕墙安装
HP-GI series of equipment are widely used in glass transition and glass curtain wall installation.
- 采用直流真空泵+直流电池，在使用过程中，无需另外接气源或电源
DC vacuum pump + DC battery are adopted; When using, there is no need to connect other air source or power source.
- 数显式真空压力开关及电池电量表，能更清楚的监测设备安全运转
Digital display vacuum pressure switch and battery charge indicator, which can monitor safe operation of equipment more clearly.
- 设备自带真空补压系统，可保证玻璃在搬运过程中整个真空系统维持在一个相对恒定的安全压力值
With vacuum pressure charging system, equipment can ensure the whole vacuum system within a relatively constant safe pressure value during transition.

	产品名称及型号 Product&Model	HP-GI500-1S
	安全载重 Safety Loading	500KG
	外型尺寸(mm) Size	800x400x260
	吸盘直径(mm) Sucker Diameter	800x400
	吸盘个数 Sucker Number	1个
	电源系统 Power System	DC12V
	控制方式 Control Mode	手动/遥控
	功能 Function	手动360度旋转以及90度翻转 Rotating 360 Degree (Manual) and Tilting 90 degree (Manual)



室外单元板块幕墙安装
直流单爪吸吊设备 HP-GI500-1S (500KG)



室外单元板块幕墙安装
直流单爪吸吊设备 HP-GI500-1S (500KG)