



■ Main Truck Specifications

Specifications		SOCMA													
				FD50	FD60	FD70	FD80	FD100							
1	Manufacturer	SOCMA													
2	Model			FD50	FD60	FD70	FD80	FD100							
3	Load capacity	kg		5000	6000	7000	8000	10000							
4	Load center	mm		600	600	600	600	600							
5	Power unit			diesel	diesel	diesel	diesel	diesel							
6	Operator type			driver / seat	driver / seat	driver / seat	driver / seat	driver / seat							
7	Tire type	front / rear		pneumatic	pneumatic	pneumatic	pneumatic	pneumatic							
8	Wheels	front / rear		4×2	4×2	4×2	4×2	4×2							
Dimensions		9	Max.lifting height	mm	3000	3000	3000	3000	3000						
		10	Free lift	mm	205	205	210	205	205						
		11	Fork size	L×W×T	mm	1220×150×60	1220×150×60	1220×150×65	1220×170×75	1220×175×75					
		12	Tilt angle	forward / backward	deg	6 / 12	6 / 12	6 / 12	6 / 12	6 / 12					
		13	Overall length(without fork)	mm		3455	3530	3590	3740	4255					
		14	Total width	mm		1995	1995	1995	1995	2245					
		15	Mast height(fork lowering)	mm		2500	2500	2500	2625	2850					
		16	Overall height fork raised	mm		4420	4420	4420	4545	4330					
		17	Height of head guard	mm		2450	2450	2450	2450	2560					
		18	Turning radius(outside)	mm		3250	3300	3360	3550	3900					
		19	Load distance	mm		615	615	620	620	710					
		20	Right angle stacking aisle (pallet size:1100×1100 add clearance)	mm		5500	5550	5620	5770	6250					
Performance		21	Speed	Travelling	full	km/h	26	26	26	26	24				
		no load			km/h	30	30	30	30	30					
		Lifting		full	mm/s	500	500	450	450	390					
				no load	mm/s	550	550	550	550	410					
		Lowering		full	mm/s	450	450	450	450	470					
				no load	mm/s	500	500	500	500	340					
24	Max.drawbar pull	Full / no load		kg	5500/2250	5500/2250	5400 / 2200	5300 / 2150	5850 / 3200						
25	Gradeability at 1.6km/h	Full		%	37	33	29	24	22						
26	Max.gradeability	Full / no load		%	42 / 19	38 / 19	33 / 19	26 / 22	24 / 20						
Weights		27	Weight	kg		8050	8750	9450	10450	12450					
		28	Weight distribution	Full	front	kg	11710	13090	14520	16370	20160				
					rear	kg	1340	1660	1930	2080	2290				
		29		No load	front	kg	4020	3860	3760	4060	5480				
rear	kg				4030	4890	5690	6390	6970						
Chassis & Wheels		30	Tires	Number	front / rear	4 / 2		4 / 2		4 / 2					
		Size		front	8.25×15-14PR		8.25×15-14PR		8.25×15-14PR		9.00×20-14PR				
		32	rear	8.25×15-14PR		8.25×15-14PR		8.25×15-14PR		8.25×15-14PR					
		33	Wheelbase	mm		2250	2250	2250	2400	2800					
		34	Tread	Front	mm		1470	1470	1470	1470	1600				
				Rear	mm		1700	1700	1700	1700	1700				
35	Ground clearance	At lowest point(mast)		mm	190	190	190	190	245						
		Frame		mm	230	230	230	230	320						
36	Brake	Service brake		power brake		power brake		power brake		power brake					
		Parking brake		mechanical-hand lever		mechanical-hand lever		mechanical-hand lever		mechanical-hand lever					
Drive Line		37	Battery	Voltage / capacity	V/AH	2×12V-80AH		2×12V-80AH		2×12V-80AH					
		38	Engine	Model		ISUZU 6BG1	Mitsubishi S6S-T	ISUZU 6BG1	Mitsubishi S6S-T	ISUZU 6BG1	Chaochai 6102BG	ISUZU 6BG1	Chaochai 6102BG		
				Rated power	KW/rpm	82.3 / 2000	67.6 / 2300	82.3 / 2000	67.6 / 2300	82.3 / 2000	67.6 / 2300	82.3 / 2000	80.8 / 2500	82.3 / 2000	80.8 / 2500
				Rated torque	N-m/rpm	418 / 1500	293 / 1700	418 / 1500	293 / 1700	418 / 1500	293 / 1700	418 / 1500	354 / 1650	418 / 1500	354 / 1650
				Number of cylinders		6	6	6	6	6	6	6	6	6	6
Displacement	L	6.494	4.996	6.494	4.996	6.494	4.996	6.494	5.785	6.494	5.785				
39	Fuel tank capacity	L		140	140	140	140	140							
40	Transmission	Shift stage (front / rear-type)		2 / 2 —Power shift T/M		2 / 2 —Power shift T/M		2 / 2 —Power shift T/M		2 / 2 —Power shift T/M					
41	Operating pressure	Hydraulic system pressure		kg/cm ²		200		200		200					

Note: There's also Yanmar 4TNE98, Chinese Xinchai C495 diesel engine for option, and the specs will be little different.

Loading chart



Notes:

Vertical axis represents load capacity; Horizontal axis shows load center; Load center are determined from front face of the fork. Capacity based on a 1000mm cube load configuration with the center of gravity at the true center of the cube, and standard fork. The load capacity will be reduced while the mast tilt forward or loading with long fork or lifting transformable width of goods. Getting the load capacities at the various load centers timely via the load curve. SOCMA's products and specifications change without prior notice. SOCMA forklift truck has equipped with standard safety device. SOCMA is not responsible for the damage occurred by removing its safety device.

Standard equipments:

Wide view mast, Cyclone air cleaner With dust indicator, Load one-way valve, Preheat indicator, King Pin, Engine-start switch, Standard backrest, Long-life tires, Overhead guard, Oil and water separator, Power steering, Adjustable steering column, Radiator water tank, Side roller, Standard carriage, Oil temperature cooler, Headlamp and steering indicator lamp, Charge indicator lamp, Hour meter, Oil warning light of engine, Water temperature gauge, Fuel gauge, Reversing light, Electric horn, Neutral-safety switch, Paper file, Rear mirror, Tools, Reversing Buzzer, General seat.

Options:

Fire extinguisher, cab, Heater unit, Rear work light, Solid tires, Fireproof silencer, Upper exhaust pipe, Tilt cylinder jacket, Rotating warning light, LPG Conversion device, Pre-filtration air intake device.

Attachments:

Side shifter, Fork positioned, Carpet boom, Fork extension, Long fork, Flat clamp, Others.

FD50 FD60 FD70 Wide view mast VM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VM300	5000	6000	7000	3000	2500	4420	205	205	210	6 - 12	8050	8750	9450
VM330	5000	6000	7000	3300	2650	4720	205	205	210	6 - 12	8100	8800	9500
VM350	5000	6000	7000	3500	2750	4920	205	205	210	6 - 12	8130	8830	9530
VM400	5000	6000	7000	4000	3050	5420	205	205	210	6 - 12	8320	9020	9720
VM450	5000	6000	7000	4500	3300	5920	205	205	210	6 - 12	8410	9110	9810
VM500	5000	6000	7000	5000	3550	6420	205	205	210	6 - 6	8520	9220	9920
VM550	4750	5700	6600	5500	3850	6920	205	205	210	3 - 6	8720	9420	10120
VM600	4400	5400	6400	6000	4100	7420	205	205	210	3 - 6	8800	9500	10200

FD50 FD60 FD70 2 Stage free lift mast VFM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VFM220	5000	6000	7000	2200	2225	3620	855	855	860	6 - 12	7990	8690	9390
VFM300	5000	6000	7000	3000	2625	4420	1255	1255	1260	6 - 12	8110	8810	9510
VFM330	5000	6000	7000	3300	2775	4720	1405	1405	1410	6 - 12	8160	8860	9560
VFM350	5000	6000	7000	3500	2875	4920	1505	1505	1510	6 - 12	8190	8890	9590
VFM400	5000	6000	7000	4000	3175	5420	1805	1805	1810	6 - 12	8390	9090	9790
VFM450	5000	6000	7000	4500	3425	5920	2055	2055	2060	6 - 12	8470	9170	9890

FD50 FD60 FD70 3 Stage free lift mast VFHM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VFHM400	4500	5500	6200	4000	2500	5400	1130	1130	1135	6 - 10	8640	9340	10040
VFHM435	4500	5500	6200	4350	2650	5750	1255	1255	1260	6 - 10	8720	9420	10120
VFHM480	4500	5500	6200	4800	2775	6200	1405	1405	1410	6 - 10	8800	9500	10200
VFHM500	4500	5500	6200	5000	2875	6400	1505	1505	1510	6 - 10	8860	9560	10260
VFHM600	4200	5000	5500	6000	3300	7400	1930	1930	1935	3 - 6	9220	9920	10620

FD80 FD100 Wide view mast

Mast Model	Load center 600mm		Max. lift height	Mast height		Free lift with backrest	Tilt angle fwd-bwd	Weight with backrest	
	FD80	FD100		(1) fork lowered	(2) fork lift with backrest			FD80	FD100
	kg	kg		mm	mm			mm	mm
VM300	8000	10000	3000	2850	4330	205	6 - 12	10450	12450
VM350	8000	10000	3500	3100	4830	205	6 - 12	10560	12560
VM400	8000	10000	4000	3400	5330	205	6 - 12	10810	12810
VM450	8000	10000	4500	3650	5830	205	6 - 12	10920	12920
VM500	7800	10000	5000	3900	6330	205	6 - 6	11020	13020
VM550	7400	9000	5500	4200	6830	205	3 - 6	11270	13270
VM600	7000	8000	6000	4450	7330	205	3 - 6	11380	13380

Notes:
 (1) Fork lowered for FD80:-125mm;
 (2) Fork lift with backrest for FD80:+215mm;

SOCMA'S products and its specifications change without prior notice



SOCMA GROUP MACHINERY INC.

ADD:NO.57-S JUDGE JUAN LUNA ST., QUEZON CITY,PHILIPPINES
 TEL: 00639156681872
 TEL: 00639156681873
 Email: jackson@socmachinery.com
 sunny@socmachinery.com
 www.socmachinery.com
 Chinese International Department
 ADD: ROOM 3005,NO.51 YUCHENG BUILDING,DONGDU ROAD,HULI AREA,XIAMEN, FUJIAN ,CHINA

Distributor



FD Series 50-100 Counter Balanced Forklift



Three Features



1 New style environmental protection and efficient engine.

Equipped with powerful and efficient engine, suitable for the latest Chinese II emission standard and Europe III emission standard(S6ST).

2 Hydraulic steering system

Steering system with horizontal cylinder provides with fixable and convenient veer operation and maintainability.



3 Wide view mast

Preeminent front operation view with unique designed wide view mast (model VM), makes safer and more reliable operation.

