

# CNM-MSL-460S

## SLIP LOADER



### PRODUCT INFORMATION


Certification:





Engine brand	Electric/koop/Runlong/B&S
Rated power	8kw、72v、200ah/15/19.2/17kw
Number of cylinders	2
Air intake way	自然吸气
Emissions standards	欧5/EPA
Rated operating capacity	300Kg
Maximum operating capacity	400Kg
Maximum breakout force	4.5KN
Bucket capacity	0.12m <sup>3</sup>
Driving speed	0-6km/h
Total cycling time	9s
System operating pressure	17-21bar
Fuel tank capacity	10L
Operating weight	1200KG
Wheel size	18*8.5-8

Vehicle height	1300mm
Length with standard bucket	2140mm
Vehicle width (standard tire)	1050mm
Length without standard bucket	1850mm
Bucket width	1050mm
Tail length	500mm
Height at maximum extension	2400mm
Height to the the bucket pin	1870mm
Maximum height as lay the bucket flat	1720mm
Dumping height	1510mm
Discharge distance	250mm
Wheelbase	800mm
Ground clearance	110mm
The flip angle of the bucket on the ground	27°
Bucket flip angle at highest position	114°


### PRODUCT DETAIL


**1**  Koop292 Runlong and Briggs & Stratton engines or electric motors are available for selection

**3**  High-quality hydraulic cylinders, simple construction, reliable operation, no transmission clearance and smoothly

**5**  LED lights have long service life and natural lighting effect

**2**  Central control, easy to use and operate

**4**  Wear-resistant oil pipes and elastic rubber materials to ensure the elasticity of hydraulic cylinders

**6**  We have multiple accessories, versatility, quick-change mountings

