

ELECTRICAL DEWATERING PUMP - KANDA

电泵



Product Description
 IP68, INSULATION F
 HIGH CHROME IMPELLER
 SIC-SIC/SIC-SIC MECHANICAL SEAL
 WITH HEAT PROTECTOR
 8M CABLE

Model	Outlet (mm) / Max. Head (M)	Power (Hp)	Max. Capacity	Weight (kg)
KBZ21.5	50 / 22	2 (1.5kW)	27m ³ /h, 0.45m ³ /min	34.5
KBZ22.2	50 / 26	3 (2.2kW)		36
KBZ23.7	50 / 34	5 (3.7kW)	29m ³ /h, 0.48m ³ /min	60
KBZ31.5	80 / 14.5	2 (1.5Kw)	40m ³ /h, 0.67m ³ /min	34.5
KBZ32.2	80 / 21	3 (2.2Kw)	50m ³ /h, 0.83m ³ /min	36
KBZ33.7	80 / 29	5 (3.7Kw)	55m ³ /h, 0.92m ³ /min	60
KBZ35.5	80 / 32	7.5 (5.5Kw)	70m ³ /h, 1.17m ³ /min	77
KBZ43.7	100 / 18	5 (3.7Kw)	90m ³ /h, 1.5m ³ /min	61
KBZ45.5	100 / 23	7.5 (5.5Kw)	105m ³ /h, 1.75m ³ /min	78
KBZ47.5	100 / 40	10 (7.5Kw)	84m ³ /h, 1.4m ³ /min	105
KBZ411	100 / 48.5	15 (11Kw)	86.4m ³ /h, 1.44m ³ /min	130
KBZ67.5	150 / 31	10 (7.5Kw)	124.8m ³ /h, 2.08m ³ /min	106
KBZ611	150 / 32	15 (11Kw)	147m ³ /h, 2.45m ³ /min	133

