

## M18 FUEL 3/8" COMPACT IMPACT WRENCH

M18 FIW2F38

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Voltage                           | 18V                              |
| No Load Speed (rpm)               | 0-800, 0-1650,<br>0-2400, 0-1000 |
| Impact Rate                       | 0-1000, 0-2400,<br>0-3500, N/A   |
| Max. Bolt Diameter                | M18                              |
| Anvil Type (Friction Ring)        | 3/8" Square                      |
| Max. Torque (Nm)                  | 339                              |
| Weight w/ 5.0Ah Battery Pack (kg) | 1.8                              |



## M18 FUEL 1/2" COMPACT IMPACT WRENCH

M18 FIW212

|                                           |                                  |
|-------------------------------------------|----------------------------------|
| Voltage                                   | 18V                              |
| No Load Speed (rpm)                       | 0-900, 0-1650,<br>0-2400, 0-1200 |
| Impact Rate                               | 0-1000, 0-2400,<br>0-3500, N/A   |
| Max. Bolt Diameter                        | M18                              |
| Anvil Type (Friction Ring + Through Hole) | 1/2" Square                      |
| Max. Torque (Nm)                          | 339                              |
| Weight w/ 5.0Ah Battery Pack (kg)         | 1.8                              |



## M18 FUEL MID TORQUE IMPACT WRENCH

M18 FMTIW2F12

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Voltage                           | 18V                               |
| No Load Speed (rpm)               | 0-1250, 0-1950,<br>0-2575, 0-1325 |
| Impact Rate                       | 0-900, 0-2100,<br>0-3100, N/A     |
| Max. Bolt Diameter                | M22                               |
| Anvil Type (Friction Ring)        | 1/2" Square                       |
| Max. Nut Busting Torque (Nm)      | 881                               |
| Weight w/ 5.0Ah Battery Pack (kg) | 2.3                               |



## M18 FUEL 1/2" HIGH TORQUE IMPACT WRENCH

M18 FHIWF12

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Voltage                           | 18V                             |
| No Load Speed (rpm)               | 0-550, 0-1400<br>0-1750, 0-1750 |
| Impact Rate (ipm)                 | 0-950, 0-1750<br>0-2100, 0-2100 |
| Max. Bolt Diameter                | M33                             |
| Max. Nut Busting Torque (Nm)      | 1898                            |
| Max. Torque (Nm)                  | 1356                            |
| Anvil Type (Friction Ring)        | 1/2" Square                     |
| Weight w/ 5.0Ah Battery Pack (kg) | 3.3                             |



## M18 FUEL 3/4" HIGH TORQUE IMPACT WRENCH

M18 ONEFHIWF34

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Voltage                           | 18V                             |
| No Load Speed (rpm)               | 0-800, 0-1300<br>0-1800, 0-1800 |
| Impact Rate (ipm)                 | 0-850, 0-1850<br>0-2400, 0-2400 |
| Max. Bolt Diameter                | M33                             |
| Max. Nut Busting Torque (Nm)      | 2032                            |
| Max. Torque (Nm)                  | 1627                            |
| Anvil Type (Friction Ring)        | 3/4" Square                     |
| Weight w/ 5.0Ah Battery Pack (kg) | 3.5                             |



## M18 FUEL 1" HIGH TORQUE IMPACT WRENCH

M18 ONEFHIWF1

|                                           |                                   |
|-------------------------------------------|-----------------------------------|
| Voltage                                   | 18V                               |
| No Load Speed (rpm)                       | 0-950, 0-1080,<br>0-1370, 0-1670  |
| Impact Rate (ipm)                         | 0-1350, 0-1650,<br>0-2100, 0-2500 |
| Max. Bolt Diameter                        | M42                               |
| Max. Nut Busting Torque (Nm)              | 2440                              |
| Max. Torque (Nm)                          | 2033                              |
| Anvil Type (Friction Ring & Through Hole) | 1" Square                         |
| Weight w/ 8.0Ah Battery Pack (kg)         | 5.9                               |



**M12 FUEL  
BANDFILE**

M12 FBFL10

|                                   |          |
|-----------------------------------|----------|
| Voltage                           | 12V      |
| Belt Speed (High) (m/min)         | 0- 1,110 |
| Belt Speed (Low) (m/min)          | 0-552    |
| Belt Width (mm)                   | 10       |
| Belt Length (mm)                  | 330      |
| Weight w/ 4.0Ah Battery Pack (kg) | 1        |

**M18****M18 FUEL 15MM  
RANDOM ORBITAL POLISHER**

M18 FROP15

|                                   |                 |
|-----------------------------------|-----------------|
| Voltage                           | 18V             |
| No Load Speed (rpm)               | 2650-5100       |
| Backing Pad Diameter (mm)         | 125             |
| Orbit (mm)                        | 15              |
| Dimensions (mm) (L x W x H)       | 420 x 117 x 132 |
| Variable Speed                    | Yes             |
| Weight w/ 8.0Ah Battery Pack (kg) | 3.65            |

**M18 FUEL 21MM  
RANDOM ORBITAL POLISHER**

M18 FROP21

|                                   |                 |
|-----------------------------------|-----------------|
| Voltage                           | 18V             |
| No Load Speed (rpm)               | 1400-4500       |
| Backing Pad Diameter (mm)         | 150             |
| Orbit (mm)                        | 21              |
| Dimensions (mm) (L x W x H)       | 437 x 150 x 138 |
| Variable Speed                    | Yes             |
| Weight w/ 8.0Ah Battery Pack (kg) | 3.77            |

**M18 FUEL  
POLISHER**

M18 FAP180

|                                   |          |
|-----------------------------------|----------|
| Voltage                           | 18V      |
| No Load Speed (rpm)               | 360-2200 |
| Max. Backing Pad Diameter (mm)    | 125      |
| Max. Polishing Pad Diameter (mm)  | 180      |
| Spindle Size                      | M14      |
| Variable Speed                    | Yes      |
| Weight w/ 5.0Ah Battery Pack (kg) | 3.1      |

**M18  
INFLATOR**

M18 BI

|                                   |                                          |
|-----------------------------------|------------------------------------------|
| Voltage                           | 18V                                      |
| No Load Air Delivery (L/min)      | 40                                       |
| Max. Pressure (bar/ PSI)          | 10.3/ 150                                |
| Hose Length (cm)                  | 92                                       |
| Gauge Accuracy                    | +/-1 PSI                                 |
| Duty Cycle                        | 33% @80 PSI<br>(20min On/<br>40 min Off) |
| Dimensions (mm) (L x W x H)       | 350 x 160 x 190                          |
| Weight w/ 2.0Ah Battery Pack (kg) | 3.25                                     |

**M18  
HEAT GUN**

M18 BHG

|                                   |     |
|-----------------------------------|-----|
| Voltage                           | 18V |
| Temperature (°C)                  | 470 |
| Air Flow (l/min)                  | 170 |
| Length (mm)                       | 163 |
| Weight w/ 5.0Ah Battery Pack (kg) | 1.6 |

