



Technical characteristics of AGP

Brand, model
 Producer
 Type
 Maximum lifting height, m
 Arrow
 Horizontal boom departure, m
 Work area (basket)
 Basket load capacity, kg
 Basket dimensions, L*W*H mm
 Working

HORYONG SKY450SF
 HRE&L Co. LTD Yu. Korea
 Auto-hydraul lift
 Telescopic, 7 sections

Sliding, aluminum

400 or 2 people

Electrical insulation of the basket, Volt Lifting
 time of the working platform, with
 Turning radius, gr
 Bugbi ypaaneHna BBILKOH

1650-550*1100

31401045*1100

1000

90

350

Stationary

(From the closed-type operator's cabin)

Remote (wireless, 5-channel)

Longitudinal 9,150

Transverse 10,270

Support circuit, mm

AGP equipment

Remote control

-Intercom device

- Lighting system on the boom

-Drum cable extension 220V

AGP safety systems

- Platform orientation system (cradle). holding the cradle in a horizontal position;
- Limit switches that limit the singe
- Blocking the boom lift when the supports are not exposed.
- Blocking the lifting of the hydraulic support when the boom is raised;
- Emergency escape system for the landing cradle

рабочий при отказе гидросистемы:

Signal buttons on the power and lower control panels

- Анонметр

HORYONG SKY450SF

