

The **PARKOO DH-138L/D** (also identified as **CDS1382E**) is a high-capacity industrial/commercial dehumidifier designed for large spaces such as warehouses, factories, and commercial basements.

## Core Specifications

- **Dehumidification Capacity:** 138 liters per day (approx. 291 pints/day) under optimal conditions of 30°C and 80% RH.
- **Coverage Area:** Effective for large spaces typically ranging from **130 to 250 m<sup>2</sup>**.
- **Power Supply:** Standard **220V/50Hz** (some variants support 110V/60Hz).
- **Rated Power:** Approximately **2000W** (2.0 kW).
- **Airflow Volume:** ~1725 m<sup>3</sup>/h.
- **Refrigerant:** Typically uses **R410a** or **R290**.

## Key Features

- **Industrial Mobility:** Equipped with a portable handle and strong wheels (2 universal front wheels and 2 larger rear wheels) for movement across rough terrain.
- **Intelligent Control:** Features a digital LCD display for precise humidity settings (30–80% or 40–90% RH depending on specific sub-model), a 24-hour timer, and fault code display for troubleshooting.
- **Drainage Options:** Supports direct hose drainage or integrated pump drainage.
- **Protection Systems:** Includes an automatic defrosting function for low-temperature operation (typically below 18°C) and a 3-minute delay protection for the compressor.
- **Build Quality:** Often features a robust metal casing with anti-corrosion coating to withstand harsh industrial environments.