

# CNM-MSL-750T

## SLIP LOADER



### PRODUCT INFORMATION

Certification:



Engine brand	Electric / Laidong 385 / Yanmar 380
Rated power	8kw、72v、20ah/18.6/18.4kw
Number of cylinders	3
Air intake way	Naturally Aspirated
Emissions standards	EURO5/EPA
Rated operating capacity	400Kg
Maximum operating capacity	450Kg
Maximum breakout force	4.5KN
Bucket capacity	0.15m <sup>3</sup>
Driving speed	0-6km/h
Total cycling time	9s
System operating pressure	25bar
Fuel tank capacity	30L
Operating weight	1200KG
Track model	180*72*45

Vehicle height	1550mm
Length with standard bucket	2700mm
Vehicle width (standard tire)	970mm
Length without standard bucket	2070mm
Bucket width	1270mm
Tail length	500mm
Height at maximum extension	2920mm
Height to the the bucket pin	2300mm
Maximum height as lay the bucket flat	2140mm
Dumping height	1700mm
Discharge distance	150mm
Track contact with ground length	1300mm
Ground clearance	240mm
The flip angle of the bucket on the ground	27°
Bucket flip angle at highest position	114°

### PRODUCT DETAIL

**1**  It is equipped with the Yanmar 3TNV80 three-cylinder water-cooled engine, which has sufficient horsepower.

**3**  High-quality hydraulic cylinders, simple construction, reliable operation, no transmission clearance and smoothly

**5**  LED lights have long service life and natural lighting effect

**2**  Hydraulic pilot operation, which is easy to use and more flexible.

**4**  Wear-resistant oil pipes and elastic rubber materials to ensure the elasticity of hydraulic cylinders

**6**  We have multiple accessories, versatility, quick-change mountings







