

Wellpoint Dewatering Pump


Carrier
Rental Systems

- Diesel
- Electric
- Super Silent
- Q Pack (quiet)

6" Size

- Water
- Sludge
- Oil/Fuel
- Chemical
- Sewage

OP150



This 6" OP150 is a robust, closed impeller type, vacuum assisted and self priming pump with large displacement, is especially designed for strenuous duty providing continuous reliable operation and high efficiency. It is also used in applications requiring greater suction lifts (up to 8.8m) and higher air evacuation, i.e. well-point dewatering.

Accessories



✓ Strainer



✓ Fuel Tank



✓ Hoses



✓ Adaptors



Discharge/Suction pipe connections	6" (150mm)
Vacuum Pump CFM	70
Water Flow	400m ³ /hr
Total Head	35m
Vacuum Lift	9m
Motor Power	38Hp
Engine - Kirloskar with electric & manual start	HA 394
Engine - Deutz	F3L912
Engine Speed	1800rpm
Shipping Dimensions	221 x 116 x 172
FOB Weight	1250kg

Diesel & Electric Range

High Head Range

Electric Submersible Range

Wellpointing

Hoses

Adaptors

Pump Selection Guide

Chiller Rental

Air Conditioning Rental

Chiller Selection Guide

