


ELECTRIC POWERED FORKLIFT

8FB 1.0 to 3.5 Ton Series



 **TOYOTA**

1,000 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	TOYOTA	1
2	Model			8FB10	8FBH10	2
3	Load Capacity	kg		1000	1000	3
4	Load Center	mm		500	500	4
5	Power Type			Battery	Battery	5
6	Operator Position			Rider Seated	Rider Seated	6
7	Tire Type	Front/Rear		Pneumatic	Pneumatic	7
8	Wheels (x = driven)	Front/Rear		2x/2	2x/2	8
9	Maximum Fork Height (MFH)	mm		3000	3000	9
10	Free Lift	mm		140	140	10
13	Fork Size	L x W x T	mm	1070/100/30	1070/100/30	13
	Lateral Fork Adjustment	MAX./MIN.	mm	920/200	920/200	
14	Tilt Range	FWD/BWD	deg	7/11	7/11	14
15	Length to Fork Face		mm	2075	2075	15
16	Overall Width		mm	1060	1060	16
17	Mast Lowered Height		mm	1970	1970	17
18	Mast Extended Height		mm	4220	4220	18
19	Overhead Guard Height		mm	2025	2105	19
21	Turning Radius (Outside)		mm	1750	1750	21
22	Load Distance (Centerline of front axle to front face of forks)		mm	400	400	22
	Rear Overhang		mm	265	265	
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2150	2150	23
	Intersecting Aisle Width		mm	1705	1705	
24		Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	14.5/14.5
			No Load	km/h	17.0/17.0	17.0/17.0
25	Speeds *	Lifting	Full Load	mm/sec	470	470
			No Load	mm/sec	650	650
26		Lowering	Full Load	mm/sec	500	500
			No Load	mm/sec	550	550
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	9260/8650 (940/880)	9220/8610(940/870)
			5-Minute Ratings	N (kg)	9260/8650(940/880)	9220/8610(940/870)
			60-Minute Ratings	N (kg)	2750/2750(280/280)	2750/2750(280/280)
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	26/26	23/26
			5-Minute Ratings	% (tanθ)	26/26	23/26
			30-Minute Ratings	% (tanθ)	14/19	14/19
32	Total Weight	Without Battery	kg	1940	2005	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	2950	3090
			Rear	kg	570	760
34		No Load	Front	kg	1310	1450
			Rear	kg	1210	1400
35		Number	Front/Rear		2/2	35
36	Tires	Size	Front		6.00-9-10-PR (I)	6.00-9-10-PR (I)
37			Rear		5.00-8-8PR (I)	5.00-8-8PR (I)
38	Wheelbase		mm	1410	1410	38
39	Tread		Front	mm	885	885
			Rear	mm	895	895
	Backrest Height		mm	1220	1220	
	Overhead Guard Clearance		mm	1035	1035	
	Counterweight Height		mm	1105	1140	
	Drawbar Height		mm	430	430	
	Step Height/Floor Height		mm	430/615	430/695	
40	Underclearance		Mast (Full Load)	mm	75	75
41			Center of Wheelbase (Full Load)	mm	85	85
			Drive Axle (Full Load)	mm	75	75
			Steer Axle (No Load)	mm	125	125
			Counterweight (No Load)	mm	120	120
		Minimum Under Clearance (Full Load)	mm	75(Mast)	75(Mast)	
	Grade Clearance		Frame	% (tanθ)	27	27
			Counterweight	% (tanθ)	65	65
42	Brake	Service (Foot)			Hydraulic	Hydraulic
43			Parking			Hand
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/330	48/545
			High	V/AH	48/485	-
46		Weight (STD Capacity Type)	kg	580	845	46
47	Electric Motors	Drive		kW	7.6	7.6
48			Load Handling	kW	9.5	9.5
			Energy Consumption According to VDI Cycle **	kWh/h	3.6	3.6
54	Control Type	Drive			Trasistor inverter	Trasistor inverter
			Load Handling			Trasistor inverter
57	Operating Pressure	For Attachments	Mpa (psi)	11.8 (1700)	11.8 (1700)	57
		Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)	dB(A)	-	-	
		Vibration in accordance with in EN13059	m/s2	-	-	


NOTE: * Computed values.

** 60 VDI Work Cycles/h with Tested Load of 1000 kg.

8FB10/8FBH10

DIMENSIONAL DRAWINGS

Unit: mm
[] for 8FBH10




UNDERCLEARANCE

Unit: mm

Mast (Full Load)	75
Center of Wheelbase (Full Load)	85
Drive Axle (Full Load)	75
Steer Axle (No Load)	125
Counterweight (No Load)	120
Minimum Under Clearance (Full Load)	75(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	1000	1000	1000	1000	1000	950
	600	900	900	900	900	900	850
	700	810	810	810	810	810	770
	800	750	750	750	750	750	710
	900	690	690	690	690	690	650
	1000	640	640	640	640	640	610
	1100	600	600	600	600	600	570
Dual Tire	1200	560	560	560	560	560	530
	500	1000	1000	1000	1000	1000	1000
	600	900	900	900	900	900	900
	700	810	810	810	810	810	810
	800	750	750	750	750	750	750
	900	690	690	690	690	690	690
	1000	640	640	640	640	640	640
1100	600	600	600	600	600	600	
1200	560	560	560	560	560	560	

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	950	900	900	900	850	750	600
	600	850	810	810	810	760	670	540
	700	780	730	730	730	690	610	490
	800	710	670	670	670	640	560	450
	900	660	620	620	620	590	520	410
	1000	610	580	580	580	550	480	380
	1100	570	540	540	540	510	450	360
Dual Tire	1200	530	510	510	510	480	420	340
	500	950	900	900	900	850	850	800
	600	850	810	810	810	760	760	720
	700	780	730	730	730	690	690	650
	800	710	670	670	670	640	640	600
	900	660	620	620	620	590	590	500
	1000	610	580	580	580	550	550	510
1100	570	540	540	540	510	510	480	
1200	530	510	510	510	510	480	480	

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	2500	1720	3110	3720	140	140	7	11	1000	1000
	2700	1820	3310	3920	140	140	7	11	1000	1000
	3000	1970	3610	4220	140	140	7	11	1000	1000
	3300	2120	3910	4520	140	140	7	11	1000	1000
	3500	2220	4110	4720	140	140	7	11	1000	1000
	3700	2380	4310	4920	140	140	7	11	1000	1000
	4000	2570	4610	5220	140	140	7	11	1000	1000
	4500	2820	5110	5720	140	140	7	5	1000	1000
	5000	3070	5610	6220	140	140	7	5	950	1000
	Wide Visible Full-Free Lift Two-Stage Mast (FV)	3000	1970	3570	4220	1400*	750*	7	11	1000
3300		2120	3870	4520	1550*	900*	7	11	1000	1000
3500		2220	4070	4720	1650*	1000*	7	11	1000	1000
3700		2380	4270	4920	1810*	1160*	7	11	1000	1000
4000		2570	4570	5220	2000*	1350*	7	11	1000	1000
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	3700	1770	4245	4920	1230*	550*	7	5	950	950
	4000	1870	4545	5220	1330*	650*	7	5	900	900
	4300	1970	4845	5520	1430*	750*	7	5	900	900
	4500	2040	5045	5720	1500*	820*	7	5	900	900
	4700	2120	5245	5920	1580*	900*	7	5	900	900
	5000	2220	5545	6220	1680*	1000*	7	5	850	850
	5500	2380	6045	6720	1840*	1160*	7	5	750	850
	6000	2570	6545	7220	2030*	1350*	7	5	600	800

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 6.50-10-12PR, plus 25mm.

1,350 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	TOYOTA	1
2	Model			8FB14	8FBH14	2
3	Load Capacity		kg	1350	1350	3
4	Load Center		mm	500	500	4
5	Power Type			Battery	Battery	5
6	Operator Position			Rider Seated	Rider Seated	6
7	Tire Type		Front/Rear	Pneumatic	Pneumatic	7
8	Wheels (x = driven)		Front/Rear	2x/2	2x/2	8
9	Maximum Fork Height (MFH)		mm	3000	3000	9
10	Free Lift		mm	145	145	10
13	Fork Size		L x W x T	1070/100/35	1070/100/35	13
	Lateral Fork Adjustment		MAX./MIN.	920/200	920/200	
14	Tilt Range		FWD/BWD	deg	7/11	14
15	Length to Fork Face		mm	2080	2080	15
16	Overall Width		mm	1060	1060	16
17	Mast Lowered Height		mm	1970	1970	17
18	Mast Extended Height		mm	4220	4220	18
19	Overhead Guard Height		mm	2025	2105	19
21	Turning Radius (Outside)		mm	1760	1760	21
22	Load Distance (Centerline of front axle to front face of forks)		mm	405	405	22
	Rear Overhang		mm	265	265	
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2165	2165	23
	Intersecting Aisle Width		mm	1725	1725	
24		Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	24
			No Load	km/h	17.0/17.0	
25	Speeds *	Lifting	Full Load	mm/sec	430	25
			No Load	mm/sec	650	
26		Lowering	Full Load	mm/sec	500	26
			No Load	mm/sec	550	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	9200/8640(930/880)	9150/8600(930/870)
			5-Minute Ratings	N (kg)	9200/8640 (930/880)	9150/8600(930/870)
			60-Minute Ratings	N (kg)	2750/2750 (280/280)	2750/2750 (280/280)
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	22/26	21/25
			5-Minute Ratings	% (tanθ)	22/26	21/25
			30-Minute Ratings	% (tanθ)	13/19	13/19
32	Total Weight	Without Battery	kg	2030	2075	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	3550	3680
			Rear	kg	410	590
34		No Load	Front	kg	1330	1460
			Rear	kg	1280	1460
35		Number	Front/Rear		2/2	35
36	Tires	Size	Front		6.00-9-10-PR (I)	6.00-9-10-PR (I)
37			Rear		5.00-8-8PR (I)	5.00-8-8PR (I)
38	Wheelbase		mm	1410	1410	38
39	Tread		Front	mm	885	885
			Rear	mm	895	895
	Backrest Height		mm	1220	1220	
	Overhead Guard Clearance		mm	1035	1035	
	Counterweight Height		mm	1105	1140	
	Drawbar Height		mm	430	430	
	Step Height/Floor Height		mm	430/615	430/695	
40	Underclearance	Mast (Full Load)		mm	70	65
41		Center of Wheelbase (Full Load)		mm	85	85
		Drive Axle (Full Load)		mm	70	65
		Steer Axle (No Load)		mm	125	125
		Counterweight (No Load)		mm	120	120
		Minimum Under Clearance (Full Load)		mm	70(Mast)	65(Mast)
	Grade Clearance	Frame		% (tanθ)	27	27
		Counterweight		% (tanθ)	65	65
42	Brake	Service (Foot)			Hydraulic	Hydraulic
43		Parking			Hand	Hand
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/330	48/545
			High	V/AH	48/485	-
46	Weight (STD Capacity Type)		kg	580	845	46
47	Electric Motors	Drive		kW	7.6	7.6
48		Load Handling		kW	9.5	9.5
		Energy Consumption According to VDI Cycle **		kWh/h	3.8	3.8
54	Control Type	Drive			Trasistor inverter	Trasistor inverter
		Load Handling			Trasistor inverter	Trasistor inverter
57	Operating Pressure	For Attachments	Mpa (psi)	11.8 (1700)	11.8 (1700)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB(A)	-	-	
	Vibration in accordance with in EN13059		m/s2	-	-	


NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 1350 kg.

8FB14/8FBH14

DIMENSIONAL DRAWINGS

Unit: mm
[] for 8FBH14




UNDERCLEARANCE

Unit: mm

Mast (Full Load)	70 [65]
Center of Wheelbase (Full Load)	85
Drive Axle (Full Load)	70 [65]
Steer Axle (No Load)	125
Counterweight (No Load)	120
Minimum Under Clearance (Full Load)	70 [65] (Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire	500	1350	1350	1350	1350	1350	1250	1150
	600	1210	1210	1210	1210	1210	1120	1030
	700	1100	1100	1100	1100	1100	1020	940
	800	1010	1010	1010	1010	1010	930	860
	900	930	930	930	930	930	860	790
	1000	860	860	860	860	860	800	740
Dual Tire	1100	810	810	810	810	810	750	690
	1200	760	760	760	760	760	700	640
	500	1350	1350	1350	1350	1350	1250	1200
	600	1210	1210	1210	1210	1210	1120	1080
	700	1100	1100	1100	1100	1100	1020	980
	800	1010	1010	1010	1010	1010	930	900
Dual Tire	900	930	930	930	930	930	860	830
	1000	860	860	860	860	860	800	770
	1100	810	810	810	810	810	750	720
	1200	760	760	760	760	760	700	670

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	1250	1200	1200	1150	1150	1000	800	650
	600	1120	1080	1080	1030	1030	900	720	580
	700	1020	980	980	940	940	820	650	530
	800	940	900	900	860	860	750	600	490
	900	870	830	830	800	800	690	550	450
	1000	810	770	770	740	740	640	510	420
Dual Tire	1100	750	720	720	690	690	600	480	390
	1200	710	680	680	650	650	560	450	360
	500	1250	1200	1200	1150	1150	1100	1100	1050
	600	1120	1080	1080	1030	1030	990	990	940
	700	1020	980	980	940	940	900	900	860
	800	940	900	900	860	860	830	830	790
Dual Tire	900	870	830	830	800	800	760	760	730
	1000	810	770	770	740	740	710	710	680
	1100	750	720	720	690	690	660	660	630
	1200	710	680	680	650	650	620	620	590

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	mm	mm	mm	mm	mm	mm	deg	deg	kg	kg
	2500	1720	3105	3720	145	145	7	11	1350	1350
	2700	1820	3305	3920	145	145	7	11	1350	1350
	3000	1970	3605	4220	145	145	7	11	1350	1350
	3300	2120	3905	4520	145	145	7	11	1350	1350
	3500	2220	4105	4720	145	145	7	11	1350	1350
	3700	2380	4305	4920	145	145	7	11	1350	1350
	4000	2570	4605	5220	145	145	7	11	1350	1350
Wide Visible Full-Free Lift Two-Stage Mast (FV)	3000	1970	3565	4220	1405*	750*	7	11	1350	1350
	3300	2120	3865	4520	1555*	900*	7	11	1350	1350
	3500	2220	4065	4720	1655*	1000*	7	11	1350	1350
	3700	2380	4265	4920	1815*	1160*	7	11	1350	1350
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2570	4565	5220	2005*	1350*	7	11	1350	1350
	3700	1770	4240	4920	1235*	550*	7	5	1250	1250
	4000	1870	4540	5220	1335*	650*	7	5	1200	1200
	4300	1970	4840	5520	1435*	750*	7	5	1200	1200
	4500	2040	5040	5720	1505*	820*	7	5	1150	1150
	4700	2120	5240	5920	1585*	900*	7	5	1150	1150
	5000	2220	5540	6220	1685*	1000*	7	5	1000	1100
	5500	2380	6040	6720	1845*	1160*	7	5	800	1100
6000	2570	6540	7220	2035*	1350*	7	5	650	1050	

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 6.50-10-12PR, plus 25mm.

1,500 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	TOYOTA	1	
2	Model			8FB15	8FBH15	2	
3	Load Capacity		kg	1500	1500	3	
4	Load Center		mm	500	500	4	
5	Power Type			Battery	Battery	5	
6	Operator Position			Rider Seated	Rider Seated	6	
7	Tire Type		Front/Rear	Pneumatic	Pneumatic	7	
8	Wheels (x = driven)		Front/Rear	2x/2	2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	3000	9	
10	Free Lift		mm	145	145	10	
13	Fork Size		L x W x T	1070/100/35	1070/100/35	13	
	Lateral Fork Adjustment		MAX./MIN.	920/200	920/200		
14	Tilt Range		FWD/BWD	7/11	7/11	14	
15	Length to Fork Face		mm	2080	2080	15	
16	Overall Width		mm	1115	1115	16	
17	Mast Lowered Height		mm	1970	1970	17	
18	Mast Extended Height		mm	4220	4220	18	
19	Overhead Guard Height		mm	2025	2105	19	
21	Turning Radius (Outside)		mm	1770	1770	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	405	405	22	
	Rear Overhang		mm	265	265		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2175	2175	23	
	Intersecting Aisle Width		mm	1760	1760		
24	Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	14.5/14.5	24	
		No Load	km/h	17.0/17.0	17.0/17.0		
25	Lifting	Full Load	mm/sec	420	420	25	
		No Load	mm/sec	650	650		
26	Lowering	Full Load	mm/sec	500	500	26	
		No Load	mm/sec	550	550		
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	9150/8620 (930/870)	9120/8590 (930/870)	27
			5-Minute Ratings	N (kg)	9150/8620 (930/870)	9120/8590 (930/870)	
			60-Minute Ratings	N (kg)	2750/2750 (280/280)	2750/2750 (280/280)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	20/25	19/25	29
			5-Minute Ratings	% (tanθ)	20/25	19/25	
			30-Minute Ratings	% (tanθ)	12/19	12/19	
32	Total Weight	Without Battery	kg	2060	2155	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	3790	3920	33
			Rear	kg	450	580	
34	No Load	Front	kg	1330	1460	34	
		Rear	kg	1410	1540		
35	Number	Front/Rear		2/2	2/2	35	
36	Tires	Front		6.00-9-10-PR (I)	6.00-9-10-PR (I)	36	
37		Rear		5.00-8-8PR (I)	5.00-8-8PR (I)		
38	Wheelbase		mm	1410	1410	38	
39	Tread	Front	mm	960	960	39	
		Rear	mm	895	895		
	Backrest Height		mm	1220	1220		
	Overhead Guard Clearance		mm	1035	1035		
	Counterweight Height		mm	1105	1140		
	Drawbar Height		mm	430	430		
	Step Height/Floor Height		mm	430/615	430/695		
40	Underclearance	Mast (Full Load)	mm	65	65	40	
41		Center of Wheelbase (Full Load)	mm	85	85		41
		Drive Axle (Full Load)	mm	65	65		
		Steer Axle (No Load)	mm	125	125		
		Counterweight (No Load)	mm	120	120		
		Minimum Under Clearance (Full Load)	mm	65(Mast)	65(Mast)		
	Grade Clearance	Frame	% (tanθ)	27	27		
		Counterweight	% (tanθ)	65	65		
42	Brake	Service (Foot)		Hydraulic	Hydraulic	42	
43		Parking		Hand	Hand		
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/400	48/545	45
		High	V/AH	48/485	-		
46	Weight (STD Capacity Type)		kg	680	845	46	
47	Electric Motors	Drive	kW	7.6	7.6	47	
48		Load Handling	kW	9.5	9.5		48
		Energy Consumption According to VDI Cycle **	kWh/h	3.9	4.0		
54	Control Type	Drive		Trasistor inverter	Trasistor inverter	54	
		Load Handling		Trasistor inverter	Trasistor inverter		
57	Operating Pressure	For Attachments	Mpa (psi)	11.8 (1700)	11.8 (1700)	57	
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB(A)	68	68		
	Vibration in accordance with in EN13059		m/s2	1.5	1.5		


NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 1500 kg.

8FB15/8FBH15

DIMENSIONAL DRAWINGS

Unit: mm
[] for 8FBH15




UNDERCLEARANCE

Unit: mm

Mast (Full Load)	65
Center of Wheelbase (Full Load)	85
Drive Axle (Full Load)	65
Steer Axle (No Load)	125
Counterweight (No Load)	120
Minimum Under Clearance (Full Load)	65(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	1500	1500	1500	1500	1450	1350
	600	1350	1350	1350	1350	1300	1210
	700	1220	1220	1220	1220	1180	1100
	800	1120	1120	1120	1120	1080	1010
	900	1040	1040	1040	1040	1000	930
	1000	960	960	960	960	930	860
	1100	900	900	900	900	870	810
Dual Tire	1200	840	840	840	840	810	760
	500	1500	1500	1500	1500	1450	1400
	600	1350	1350	1350	1350	1300	1260
	700	1220	1220	1220	1220	1180	1140
	800	1120	1120	1120	1120	1080	1050
	900	1040	1040	1040	1040	1040	970
	1000	960	960	960	960	960	900
1100	900	900	900	900	900	870	840
1200	840	840	840	840	840	810	780

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	1400	1400	1400	1350	1350	1200	900
	600	1260	1260	1260	1210	1210	1080	810
	700	1150	1150	1150	1100	1100	980	730
	800	1050	1050	1050	1010	1010	900	670
	900	970	970	970	940	940	830	620
	1000	900	900	900	870	870	770	580
	1100	840	840	840	810	810	720	540
Dual Tire	1200	790	790	790	760	760	680	510
	500	1400	1400	1400	1350	1350	1300	1250
	600	1260	1260	1260	1210	1210	1170	1120
	700	1150	1150	1150	1100	1100	980	730
	800	1120	1050	1050	1010	1010	1060	1020
	900	970	970	970	940	940	900	870
	1000	900	900	900	870	870	840	810
1100	840	840	840	810	810	780	750	
1200	790	790	790	760	760	730	710	

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual	
			Without Load Backrest	With Standard Load Backrest							deg
Wide Visible Mast (V)	2500	1720	3105	3720	145	145	7	11	1500	1500	
	2700	1820	3305	3920	145	145	7	11	1500	1500	
	3000	1970	3605	4220	145	145	7	11	1500	1500	
	3300	2120	3905	4520	145	145	7	11	1500	1500	
	3500	2220	4105	4720	145	145	7	11	1500	1500	
	3700	2380	4305	4920	145	145	7	11	1500	1500	
	4000	2570	4605	5220	145	145	7	11	1500	1500	
	4500	2820	5105	5720	145	145	7	5	1450	1450	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3070	5605	6220	145	145	7	5	1350	1400	
	3000	1970	3565	4220	1405*	750*	7	11	1500	1500	
	3300	2120	3865	4520	1555*	900*	7	11	1500	1500	
	3500	2220	4065	4720	1655*	1000*	7	11	1500	1500	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	3700	2380	4265	4920	1815*	1160*	7	11	1500	1500	
	4000	2570	4565	5220	2005*	1350*	7	11	1500	1500	
	3700	1770	4240	4920	1235*	550*	7	5	1400	1400	
	4000	1870	4540	5220	1335*	650*	7	5	1400	1400	
	4300	1970	4840	5520	1435*	750*	7	5	1400	1400	
	4500	2040	5040	5720	1505*	820*	7	5	1350	1350	
4700	2120	5240	5920	1585*	900*	7	5	1350	1350		
5000	2220	5540	6220	1685*	1000*	7	5	1200	1300		
5500	2380	6040	6720	1845*	1160*	7	5	1100	1250		
6000	2570	6540	7220	2035*	1350*	7	5	900	1100		

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 6.50-10-12PR, plus 25mm.

1,500 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	1	
2	Model			40-8FB15	2	
3	Load Capacity		kg	1500	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type	Front/Rear		Pneumatic	7	
8	Wheels (x = driven)	Front/Rear		2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	125	10	
13	Fork Size	L x W x T	mm	1070/100/35	13	
	Fork Spread (Outside)	MAX./MIN.	mm	920/200		
14	Tilt Range	FWD/BWD	deg	7/11	14	
15	Length to Fork Face		mm	2215	15	
16	Overall Width		mm	1160	16	
17	Mast Lowered Height		mm	1975	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height		mm	2105	19	
21	Turning Radius (Outside)		mm	1980	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	415	22	
	Rear Overhang		mm	300		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2395	23	
	Intersecting Aisle Width		mm	1825		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.0/14.0	24
			No Load	km/h	16.0/16.0	
		Lowering	Full Load	mm/sec	380	25
			No Load	mm/sec	600	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	11330/10640 (1150/1080)	27
			5-Minute Ratings	N (kg)	11330/10640 (1150/1080)	
			60-Minute Ratings	N (kg)	4710/4900 (480/500)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	24/25	29
			5-Minute Ratings	% (tanθ)	24/25	
			30-Minute Ratings	% (tanθ)	17/25	
32	Total Weight	Without Battery	kg	2475	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	4080	33
			Rear	kg	850	
34		No Load	Front	kg	1670	34
			Rear	kg	1760	
35		Number	Front/Rear		2/2	35
36	Tires		Front		21X8-9-14PR (I)	36
37			Size	Rear		18X7-8-14PR (I)
38	Wheelbase		mm	1500	38	
39	Tread	Front	mm	970	39	
		Rear	mm	940		
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1135		
	Drawbar Height			280		
	Step Height/Floor Height			435/700		
40	Underclearance	Mast (Full Load)	mm	75	40	
41		Center of Wheelbase (Full Load)	mm	90	41	
		Drive Axle (Full Load)	mm	75		
		Steer Axle (No Load)	mm	120		
		Counterweight (No Load)	mm	115		
		Minimum Under Clearance (Full Load)	mm	75(Mast)		
	Grade Clearance	Frame	% (tanθ)	25		
		Counterweight	% (tanθ)	63		
42	Brake	Service (Foot)		Hydraulic	42	
43		Parking			Hand	43
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/600	45
		High	V/AH	48/730		
46		Weight (STD Capacity Type)	kg	955	46	
47	Electric Motors	Drive	kW	10.7	47	
48		Load Handling	kW	12.2	48	
		Energy Consumption According to VDI Cycle **	kWh/h	4.3		
54	Control Type	Drive		Transistor inverter	54	
		Load Handling		Transistor inverter		
57	Operating Pressure	For Attachments	Mpa (psi)	14.7 (2100)	57	
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)	-		
	Vibration in accordance with in EN13059		m/s2	-		

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 1500 kg.

DIMENSIONAL DRAWINGS

Unit: mm




UNDERCLEARANCE

Unit: mm

Mast (Full Load)	75
Center of Wheelbase (Full Load)	90
Drive Axle (Full Load)	75
Counterweight (No Load)	120
Steer Axle (No Load)	115
Minimum Under Clearance (No Load)	75 (Frame)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	1500	1500	1500	1500	1450	1350
	600	1350	1350	1350	1350	1300	1210
	700	1230	1230	1230	1230	1190	1100
	800	1120	1120	1120	1120	1090	1010
	900	1040	1040	1040	1040	1000	930
	1000	970	970	970	970	930	870
Dual Tire	1100	900	900	900	900	870	810
	1200	850	850	850	850	820	760
	500	1500	1500	1500	1500	1450	1400
	600	1350	1350	1350	1350	1300	1260
	700	1230	1230	1230	1230	1190	1140
	800	1120	1120	1120	1120	1090	1050
Dual Tire	900	1040	1040	1040	1040	1000	975
	1000	970	970	970	970	930	900
	1100	900	900	900	900	870	840
	1200	850	850	850	850	820	790

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	1400	1400	1400	1350	1350	1200	1100
	600	1260	1260	1260	1220	1220	1080	990
	700	1150	1150	1150	1110	1110	990	900
	800	1060	1060	1060	1020	1020	910	830
	900	980	980	980	940	940	840	770
	1000	910	910	910	880	880	780	710
Dual Tire	1100	850	850	850	820	820	730	670
	1200	800	800	800	770	770	680	630
	500	1400	1400	1400	1350	1350	1300	1250
	600	1260	1260	1260	1220	1220	1170	1130
	700	1150	1150	1150	1110	1110	1070	1030
	800	1060	1060	1060	1020	1020	980	940
Dual Tire	900	980	980	980	940	940	910	870
	1000	910	910	910	880	880	840	810
	1100	850	850	850	820	820	790	760
	1200	800	800	800	770	770	740	710

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
mm	mm	mm	mm	mm	mm	deg	deg	kg	kg	
Wide Visible Mast (V)	2500	1725	3170	3720	125	125	7	11	1500	1500
	2700	1825	3370	3920	125	125	7	11	1500	1500
	3000	1975	3670	4220	125	125	7	11	1500	1500
	3300	2125	3970	4520	125	125	7	11	1500	1500
	3500	2225	4170	4720	125	125	7	11	1500	1500
	3700	2385	4370	4920	125	125	7	11	1500	1500
	4000	2575	4670	5220	125	125	7	11	1500	1500
	4500	2825	5170	5720	125	125	7	5	1450	1450
Wide Visible Full-Free Lift Two-Stage Mast (FV)	3000	1975	3605	4220	1370*	755*	7	11	1500	1500
	3300	2125	3905	4520	1520*	905*	7	11	1500	1500
	3500	2225	4105	4720	1620*	1005*	7	11	1500	1500
	3700	2385	4305	4920	1780*	1165*	7	11	1500	1500
	4000	2575	4605	5220	1970*	1355*	7	11	1500	1500
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	3700	1775	4345	4920	1130*	555*	7	5	1400	1400
	4000	1875	4645	5220	1230*	655*	7	5	1400	1400
	4300	1975	4945	5520	1330*	755*	7	5	1400	1400
	4500	2045	5145	5720	1400*	825*	7	5	1350	1350
	4700	2125	5345	5920	1480*	905*	7	5	1350	1350
	5000	2225	5645	6220	1580*	1005*	7	5	1200	1300
	5500	2385	6145	6720	1740*	1165*	7	5	1100	1250
	6000	2575	6645	7220	1930*	1355*	7	5	900	1100

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 23x9-10-16PR, plus 20mm.

1,750 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	TOYOTA	1
2	Model			8FB18	8FBH18	2
3	Load Capacity		kg	1750	1750	3
4	Load Center		mm	500	500	4
5	Power Type			Battery	Battery	5
6	Operator Position			Rider Seated	Rider Seated	6
7	Tire Type		Front/Rear	Pneumatic	Pneumatic	7
8	Wheels (x = driven)		Front/Rear	2x/2	2x/2	8
9	Maximum Fork Height (MFH)		mm	3000	3000	9
10	Free Lift		mm	145	145	10
13	Fork Size		L x W x T	1070/100/35	1070/100/35	13
	Lateral Fork Adjustment		MAX./MIN.	920/200	920/200	
14	Tilt Range		FWD/BWD	7/11	7/11	14
15	Length to Fork Face		mm	2115	2115	15
16	Overall Width		mm	1115	1115	16
17	Mast Lowered Height		mm	1970	1970	17
18	Mast Extended Height		mm	4220	4220	18
19	Overhead Guard Height		mm	2025	2105	19
21	Turning Radius (Outside)		mm	1780	1780	21
22	Load Distance (Centerline of front axle to front face of forks)		mm	405	405	22
	Rear Overhang		mm	300	300	
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2185	2185	23
	Intersecting Aisle Width		mm	1775	1775	
24		Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	24
			No Load	km/h	17.0/17.0	
25	Speeds *	Lifting	Full Load	mm/sec	370	25
			No Load	mm/sec	650	
26		Lowering	Full Load	mm/sec	500	26
			No Load	mm/sec	550	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	9240/8620(940/870)	27
			5-Minute Ratings	N (kg)	9240/8620(940/870)	
			60-Minute Ratings	N (kg)	2750/2940(280/300)	2750/2940(280/300)
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	18/23	29
			5-Minute Ratings	% (tanθ)	18/23	
			30-Minute Ratings	% (tanθ)	11/18	11/18
32	Total Weight	Without Battery	kg	2310	2355	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	4240	33
			Rear	kg	500	620
34		No Load	Front	kg	1370	34
			Rear	kg	1620	1740
35		Number	Front/Rear		2/2	35
36	Tires	Size	Front		21X8-9-10PR (I)	36
37			Rear		5.00-8-10PR (I)	5.00-8-10PR (I)
38	Wheelbase		mm	1410	1410	38
39	Tread		Front	mm	920	39
			Rear	mm	895	895
	Backrest Height		mm	1220	1220	
	Overhead Guard Clearance		mm	1035	1035	
	Counterweight Height		mm	1105	1140	
	Drawbar Height		mm	430	430	
	Step Height/Floor Height		mm	430/615	430/695	
40	Underclearance	Mast (Full Load)		mm	65	40
41		Center of Wheelbase (Full Load)		mm	85	41
		Drive Axle (Full Load)		mm	65	
		Steer Axle (No Load)		mm	125	
		Counterweight (No Load)		mm	120	
		Minimum Under Clearance (Full Load)		mm	65(Mast)	65(Mast)
	Grade Clearance	Frame		% (tanθ)	27	
		Counterweight		% (tanθ)	54	
42	Brake	Service (Foot)			Hydraulic	42
43		Parking			Hand	43
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/400	45
		High	V/AH	48/485	-	
46	Weight (STD Capacity Type)		kg	680	845	46
47	Electric Motors	Drive		kW	7.6	47
48		Load Handling		kW	9.5	48
		Energy Consumption According to VDI Cycle **		kWh/h	4.2	4.3
54	Control Type	Drive			Trasistor inverter	54
		Load Handling			Trasistor inverter	Trasistor inverter
57	Operating Pressure	For Attachments	Mpa (psi)	11.8(1700)	11.8(1700)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)	68	68	
	Vibration in accordance with in EN13059		m/s2	1.5	1.5	


NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 1750 kg.

8FB18/8FBH18

DIMENSIONAL DRAWINGS

Unit: mm
[] for 8FBH18




UNDERCLEARANCE

Unit: mm

Mast (Full Load)	65
Center of Wheelbase (Full Load)	85
Drive Axle (Full Load)	65
Steer Axle (No Load)	125
Counterweight (No Load)	120
Minimum Under Clearance (Full Load)	65(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire	500	1750	1750	1750	1750	1750	1550	1200
	600	1570	1570	1570	1570	1570	1390	1080
	700	1430	1430	1430	1430	1430	1260	980
	800	1310	1310	1310	1310	1310	1160	900
	900	1210	1210	1210	1210	1210	1070	830
	1000	1120	1120	1120	1120	1120	990	770
	1100	1050	1050	1050	1050	1050	930	720
Dual Tire	1200	980	980	980	980	980	870	670
	500	1750	1750	1750	1750	1750	1650	1550
	600	1570	1570	1570	1570	1570	1480	1390
	700	1430	1430	1430	1430	1430	1350	1260
	800	1310	1310	1310	1310	1310	1230	1160
	900	1210	1210	1210	1210	1210	1140	1070
	1000	1120	1120	1120	1120	1120	1060	990
1100	1050	1050	1050	1050	1050	990	930	
1200	980	980	980	980	980	930	870	

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	1600	1600	1550	1500	1500	1250	900	750
	600	1440	1440	1390	1350	1350	1120	810	670
	700	1310	1310	1270	1230	1230	1020	730	610
	800	1200	1200	1170	1130	1130	940	670	560
	900	1110	1110	1080	1040	1040	870	620	520
	1000	1030	1030	1000	970	970	810	580	480
	1100	970	970	930	900	900	750	540	450
Dual Tire	1200	910	910	880	850	850	710	510	420
	500	1600	1600	1550	1500	1500	1450	1400	1150
	600	1440	1440	1390	1350	1350	1300	1260	1030
	700	1310	1310	1270	1230	1230	1190	1150	940
	800	1200	1200	1170	1130	1130	1090	1050	860
	900	1100	1100	1080	1040	1040	1010	970	800
	1000	1030	1030	1000	970	970	940	900	740
1100	970	970	930	900	900	870	840	690	
1200	910	910	880	850	850	820	790	650	

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	2500	1720	3105	3720	145	145	7	11	1750	1750
	2700	1820	3305	3920	145	145	7	11	1750	1750
	3000	1970	3605	4220	145	145	7	11	1750	1750
	3300	2120	3905	4520	145	145	7	11	1750	1750
	3500	2220	4105	4720	145	145	7	11	1750	1750
	3700	2380	4305	4920	145	145	7	11	1750	1750
	4000	2570	4605	5220	145	145	7	5<11>	1750	1750
	4500	2820	5105	5720	145	145	7	5	1550	1650
	5000	3070	5605	6220	145	145	7	5	1200	1550
Wide Visible Full-Free Lift Two-Stage Mast (FV)	3000	1970	3565	4220	1405*	750*	7	11	1750	1750
	3300	2120	3865	4520	1555*	900*	7	11	1750	1750
	3500	2220	4065	4720	1655*	1000*	7	11	1750	1750
	3700	2380	4265	4920	1815*	1160*	7	11	1750	1750
	4000	2570	4565	5220	2005*	1350*	7	5<11>	1750	1750
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	3700	1770	4240	4920	1235*	550*	7	5	1600	1600
	4000	1870	4540	5220	1335*	650*	7	5	1600	1600
	4300	1970	4840	5520	1435*	750*	7	5	1550	1550
	4500	2040	5040	5720	1505*	820*	7	5	1500	1500
	4700	2120	5240	5920	1585*	900*	7	5	1500	1500
	5000	2220	5540	6220	1685*	1000*	7	5	1250	1450
	5500	2380	6040	6720	1845*	1160*	7	5	900	1400
6000	2570	6540	7220	2035*	1350*	7	5	750	1150	

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 6.50-10-12PR, plus 25mm.
< > for dual tires.

2,000 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	TOYOTA	1
2	Model			8FB20	8FBH20	2
3	Load Capacity		kg	2000	2000	3
4	Load Center		mm	500	500	4
5	Power Type			Battery	Battery	5
6	Operator Position			Rider Seated	Rider Seated	6
7	Tire Type		Front/Rear	Pneumatic	Pneumatic	7
8	Wheels (x = driven)		Front/Rear	2x/2	2x/2	8
9	Maximum Fork Height (MFH)		mm	3000	3000	9
10	Free Lift		mm	125	125	10
13	Fork Size		L x W x T	1070/120/36	1070/120/36	13
	Lateral Fork Adjustment		MAX./MIN.	1020/240	1020/240	
14	Tilt Range		FWD/BWD	7/11	7/11	14
15	Length to Fork Face		mm	2240	2240	15
16	Overall Width		mm	1160	1160	16
17	Mast Lowered Height		mm	1975	1975	17
18	Mast Extended Height		mm	4220	4220	18
19	Overhead Guard Height		mm	2025	2105	19
21	Turning Radius (Outside)		mm	1980	1980	21
22	Load Distance (Centerline of front axle to front face of forks)		mm	420	420	22
	Rear Overhang		mm	320	320	
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2400	2400	23
	Intersecting Aisle Width		mm	1850	1850	
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	14.5/14.5
			No Load	km/h	16.5/16.5	16.5/16.5
		Lifting	Full Load	mm/sec	360	360
			No Load	mm/sec	600	600
26	Lowering	Full Load	mm/sec	500	500	
		No Load	mm/sec	500	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	11260/10640 (1140/1080)	11210/10600 (1140/1080)
			5-Minute Ratings	N (kg)	11260/10640 (1140/1080)	11210/10600 (1140/1080)
			60-Minute Ratings	N (kg)	4710/4900 (480/500)	4710/4900 (480/500)
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	22/23	20/23
			5-Minute Ratings	% (tanθ)	22/23	20/23
			30-Minute Ratings	% (tanθ)	15/22	15/22
32	Total Weight	Without Battery	kg	2580	2600	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	4800	4990
			Rear	kg	530	770
34		No Load	Front	kg	1570	1760
			Rear	kg	1760	2000
35	Tires	Number	Front/Rear	2/2	2/2	35
36	Size	Front		21X8-9-14PR (I)	21X8-9-14PR (I)	
37		Rear		18X7-8-14PR (I)	18X7-8-14PR (I)	
38	Wheelbase		mm	1500	1500	38
39	Tread	Front	mm	970	970	
		Rear	mm	940	940	
	Backrest Height		mm	1220	1220	
	Overhead Guard Clearance		mm	1035	1035	
	Counterweight Height		mm	1100	1135	
	Drawbar Height		mm	425	425	
	Step Height/Floor Height		mm	435/620	435/700	
40	Underclearance	Mast (Full Load)		mm	70	70
41		Center of Wheelbase (Full Load)		mm	90	90
		Drive Axle (Full Load)		mm	70	70
		Steer Axle (No Load)		mm	120	120
		Counterweight (No Load)		mm	115	115
		Minimum Under Clearance (Full Load)		mm	70(Mast)	70(Mast)
	Grade Clearance	Frame	% (tanθ)	25	25	
		Counterweight	% (tanθ)	56	56	
42	Brake	Service (Foot)		Hydraulic	Hydraulic	
43		Parking		Hand	Hand	
45	Battery	Voltage/Capacity (5-hour rating)	V/AH	48/450	48/730	
46		High	V/AH	48/600	-	
47	Weight (STD Capacity Type)		kg	750	1160	
48	Electric Motors	Drive		kW	10.7	10.7
		Load Handling		kW	12.2	12.2
		Energy Consumption According to VDI Cycle **		kWh/h	4.1	4.2
54	Control Type	Drive		Transistor inverter	Transistor inverter	
		Load Handling		Transistor inverter	Transistor inverter	
57	Operating Pressure	For Attachments	Mpa (psi)	14.7(2100)	14.7(2100)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB(A)	67	67	
	Vibration in accordance with in EN13059		m/s2	1.5	1.5	

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 2000 kg.

DIMENSIONAL DRAWINGS


Unit: mm
[] for 8FBH20



UNDERCLEARANCE

Mast (Full Load)	70
Center of Wheelbase (Full Load)	90
Drive Axle (Full Load)	70
Steer Axle (No Load)	120
Counterweight (No Load)	115
Minimum Under Clearance (Full Load)	70(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	2000	2000	2000	2000	1900	1650
	600	1800	1800	1800	1800	1710	1480
	700	1640	1640	1640	1640	1560	1350
	800	1500	1500	1500	1500	1430	1240
	900	1390	1390	1390	1390	1320	1150
	1000	1290	1290	1290	1290	1230	1060
	1100	1210	1210	1210	1210	1150	990
	1200	1130	1130	1130	1130	1070	930
	1300	1070	1070	1070	1070	1010	880
	Dual Tire	500	2000	2000	2000	2000	1900
600		1800	1800	1800	1800	1710	1620
700		1640	1640	1640	1640	1560	1470
800		1500	1500	1500	1500	1430	1350
900		1390	1390	1390	1390	1320	1250
1000		1290	1290	1290	1290	1230	1160
1100		1210	1210	1210	1210	1150	1080
1200		1130	1130	1130	1130	1070	1020
1300		1070	1070	1070	1070	1010	960

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000	
Single Tire	500	1900	1900	1850	1800	1800	1550	1200	900
	600	1710	1710	1670	1620	1620	1400	1080	810
	700	1560	1560	1520	1480	1480	1270	990	740
	800	1440	1440	1400	1360	1360	1170	910	680
	900	1330	1330	1300	1260	1260	1090	840	630
	1000	1240	1240	1210	1170	1170	1010	780	580
	1100	1160	1160	1130	1100	1100	940	730	550
	1200	1090	1090	1060	1030	1030	890	690	510
	1300	1030	1030	1000	970	970	840	650	480
	Dual Tire	500	1900	1900	1850	1800	1800	1750	1700
600		1710	1710	1670	1620	1620	1580	1530	1350
700		1560	1560	1520	1480	1480	1440	1400	1230
800		1440	1440	1400	1360	1360	1320	1290	1130
900		1330	1330	1300	1260	1260	1230	1190	1050
1000		1240	1240	1210	1170	1170	1140	1110	980
1100		1160	1160	1130	1100	1100	1070	1040	910
1200		1090	1090	1060	1030	1030	1000	970	860
1300		1030	1030	1000	970	970	940	920	810

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	2500	1725	3170	3720	125	125	7	11	2000	2000
	2700	1825	3370	3920	125	125	7	11	2000	2000
	3000	1975	3670	4220	125	125	7	11	2000	2000
	3300	2125	3970	4520	125	125	7	11	2000	2000
	3500	2225	4170	4720	125	125	7	11	2000	2000
	3700	2385	4370	4920	125	125	7	11	2000	2000
	4000	2575	4670	5220	125	125	7	11	2000	2000
	4500	2825	5170	5720	125	125	7	5	1900	1900
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3075	5670	6220	125	125	7	5	1650	1800
	3000	1975	3605	4220	1370*	755*	7	11	2000	2000
	3300	2125	3905	4520	1520*	905*	7	11	2000	2000
	3500	2225	4105	4720	1620*	1005*	7	11	2000	2000
	3700	2385	4305	4920	1780*	1165*	7	11	2000	2000
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2575	4605	5220	1970*	1355*	7	11	2000	2000
	3700	1775	4345	4920	1130*	555*	7	5	1900	1900
	4000	1875	4645	5220	1230*	655*	7	5	1900	1900
	4300	1975	4945	5520	1330*	755*	7	5	1850	1850
	4500	2045	5145	5720	1400*	825*	7	5	1800	1800
	4700	2125	5345	5920	1480*	905*	7	5	1800	1800
	5000	2225	5645	6220	1580*	1005*	7	5	1550	1750
	5500	2385	6145	6720	1740*	1165*	7	5	1200	1700
6000	2575	6645	7220	1930*	1355*	7	5	900	1500	

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 23x9-10-16PR, plus 20mm.

2,000 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	1	
2	Model			40-8FB20	2	
3	Load Capacity		kg	2000	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type		Front/Rear	Pneumatic	7	
8	Wheels (x = driven)		Front/Rear	2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	150	10	
13	Fork Size		L x W x T	1070/120/36	13	
	Fork Spread (Outside)		MAX./MIN.	1020/240		
14	Tilt Range		FWD/BWD	6/11	14	
15	Length to Fork Face		mm	2405	15	
16	Overall Width		mm	1230	16	
17	Mast Lowered Height		mm	1995	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height		mm	2160	19	
21	Turning Radius (Outside)		mm	2145	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	445	22	
	Rear Overhang		mm	310		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2590	23	
	Intersecting Aisle Width		mm	1910		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	24
			No Load	km/h	15.5/15.5	
		Lowering	Full Load	mm/sec	360	25
			No Load	mm/sec	600	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	12650/11980 (1290/1220)	27
			5-Minute Ratings	N (kg)	12650/11980 (1290/1220)	
			60-Minute Ratings	N (kg)	5300/5390 (540/550)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	21/24	29
			5-Minute Ratings	% (tanθ)	21/24	
			30-Minute Ratings	% (tanθ)	14/21	
32	Total Weight	Without Battery	kg	2900	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	5170	33
			Rear	kg	1050	
34		No Load	Front	kg	2020	34
			Rear	kg	2200	
35		Number	Front/Rear	2/2	35	
36	Tires	Front		7.00-12-12PR (I)	36	
37		Size	Rear		6.00-9-10PR (I)	37
38	Wheelbase		mm	1650	38	
39	Tread	Front	mm	960	39	
		Rear	mm	965		
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1195		
	Drawbar Height			505		
	Step Height/Floor Height			490/755		
40	Underclearance	Mast (Full Load)		mm	85	40
41		Center of Wheelbase (Full Load)		mm	110	41
		Drive Axle (Full Load)		mm	125	
		Steer Axle (No Load)			150	
		Counterweight (No Load)		mm	160	
		Minimum Under Clearance (Full Load)		mm	85(Mast)	
	Grade Clearance	Frame	% (tanθ)	29		
		Counterweight	% (tanθ)	96		
42	Brake	Service (Foot)		Hydraulic	42	
43		Parking		Hand	43	
45	Battery	Voltage/Capacity (5-hour rating)	STD High	V/AH V/AH	48/845 -	45
46		Weight (STD Capacity Type)	kg	1320	46	
47	Electric Motors	Drive	kW	10.7	47	
48		Load Handling	kW	12.2	48	
		Energy Consumption According to VDI Cycle **	kWh/h	4.2		
54	Control Type	Drive		Transistor inverter	54	
		Load Handling		Transistor inverter		
57	Operating Pressure	For Attachments	Mpa (psi)	14.7 (2100)	57	
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)	-		
	Vibration in accordance with in EN13059		m/s ²	-		

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 2000 kg.

DIMENSIONAL DRAWINGS


Unit: mm



UNDERCLEARANCE

Mast (Full Load)	85
Center of Wheelbase (Full Load)	110
Drive Axle (Full Load)	125
Steer Axle (No Load)	150
Counterweight (No Load)	160
Minimum Under Clearance (No Load)	85(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire	500	2000	2000	2000	2000	2000	1900	1650
	600	1810	1810	1810	1810	1810	1720	1490
	700	1650	1650	1650	1650	1650	1570	1360
	800	1520	1520	1520	1520	1520	1440	1250
	900	1410	1410	1410	1410	1410	1340	1160
	1000	1310	1310	1310	1310	1310	1250	1080
	1100	1230	1230	1230	1230	1230	1170	1010
	1200	1150	1150	1150	1150	1150	1090	950
	1300	1090	1090	1090	1090	1090	1030	900
	Dual Tire	500	2000	2000	2000	2000	2000	1900
600		1810	1810	1810	1810	1810	1720	1630
700		1650	1650	1650	1650	1650	1570	1490
800		1520	1520	1520	1520	1520	1440	1370
900		1410	1410	1410	1410	1410	1340	1270
1000		1310	1310	1310	1310	1310	1250	1180
1100		1230	1230	1230	1230	1230	1170	1100
1200		1150	1150	1150	1150	1150	1090	1040
1300		1090	1090	1090	1090	1090	1030	980

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	1900	1900	1850	1800	1800	1550	1200	900
	600	1720	1720	1670	1630	1630	1400	1080	810
	700	1570	1570	1530	1490	1490	1280	990	740
	800	1450	1450	1410	1370	1370	1180	910	680
	900	1340	1340	1310	1270	1270	1100	850	630
	1000	1250	1250	1220	1190	1190	1020	790	590
	1100	1170	1170	1140	1110	1110	960	740	550
	1200	1100	1100	1070	1040	1040	900	690	520
	1300	1040	1040	1010	990	990	850	660	490
	Dual Tire	500	1900	1900	1850	1800	1800	1750	1700
600		1720	1720	1670	1630	1630	1580	1540	1360
700		1570	1570	1530	1490	1490	1450	1410	1240
800		1450	1450	1410	1370	1370	1330	1300	1140
900		1340	1340	1310	1270	1270	1240	1200	1060
1000		1250	1250	1220	1190	1190	1150	1120	990
1100		1170	1170	1140	1110	1110	1080	1050	930
1200		1100	1100	1070	1040	1040	1020	990	870
1300		1040	1040	1010	990	990	960	930	820

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual	
			Without Load Backrest	With Standard Load Backrest							deg
Wide Visible Mast (V)	2500	1745	3160	3720	150	150	6	11	2000	2000	
	2700	1845	3360	3920	150	150	6	11	2000	2000	
	3000	1995	3660	4220	150	150	6	11	2000	2000	
	3300	2145	3960	4520	150	150	6	11	2000	2000	
	3500	2245	4160	4720	150	150	6	11	2000	2000	
	3700	2405	4360	4920	150	150	6	11	2000	2000	
	4000	2595	4660	5220	150	150	6	11	2000	2000	
	4500	2845	5160	5720	150	150	6	6	1900	1900	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3095	5660	6220	150	150	6	6	1650	1800	
	3000	1995	3600	4220	1395	775	6	11	2000	2000	
	3300	2145	3900	4520	1545	925	6	11	2000	2000	
	3500	2245	4100	4720	1645	1025	6	11	2000	2000	
	3700	2405	4300	4920	1805	1185	6	11	2000	2000	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2595	4600	5220	1995	1375	6	11	2000	2000	
	3700	1795	4270	4920	1225	575	6	6	1900	1900	
	4000	1895	4570	5220	1325	675	6	6	1900	1900	
	4300	1995	4870	5520	1425	775	6	6	1850	1850	
	4500	2065	5070	5720	1495	845	6	6	1800	1800	
	4700	2145	5270	5920	1575	925	6	6	1800	1800	
	5000	2245	5570	6220	1675	1025	6	6	1550	1750	
	5500	2405	6070	6720	1835	1185	6	6	1200	1700	
6000	2595	6570	7220	2025	1375	6	6	900	1500		

NOTE: Height of standard load backrest is 1220 mm.

2,500 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	TOYOTA	1
2	Model			8FB25	8FBH25	2
3	Load Capacity		kg	2500	2500	3
4	Load Center		mm	500	500	4
5	Power Type			Battery	Battery	5
6	Operator Position			Rider Seated	Rider Seated	6
7	Tire Type		Front/Rear	Pneumatic	Pneumatic	7
8	Wheels (x = driven)		Front/Rear	2x/2	2x/2	8
9	Maximum Fork Height (MFH)		mm	3000	3000	9
10	Free Lift		mm	130	130	10
13	Fork Size		L x W x T	1070/120/40	1070/120/40	13
	Lateral Fork Adjustment		MAX./MIN.	1020/240	1020/240	
14	Tilt Range		FWD/BWD	7/11	7/11	14
15	Length to Fork Face		mm	2290	2290	15
16	Overall Width		mm	1160	1160	16
17	Mast Lowered Height		mm	1975	1975	17
18	Mast Extended Height		mm	4220	4220	18
19	Overhead Guard Height		mm	2025	2105	19
21	Turning Radius (Outside)		mm	2000	2000	21
22	Load Distance (Centerline of front axle to front face of forks)		mm	435	435	22
	Rear Overhang		mm	355	355	
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2430	2430	23
	Intersecting Aisle Width		mm	1875	1875	
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.0/14.0	14.0/14.0
			No Load	km/h	16.0/16.0	16.0/16.0
		Lifting	Full Load	mm/sec	340	340
			No Load	mm/sec	600	600
26	Lowering	Full Load	mm/sec	500	500	
		No Load	mm/sec	500	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	11090/10560 (1130/1070)	11060/11530 (1120/1170)
			5-Minute Ratings	N (kg)	11090/10560 (1130/1070)	11060/11530 (1120/1170)
			60-Minute Ratings	N (kg)	4510/4810 (460/490)	4510/4810 (460/490)
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	18/20	17/21
			5-Minute Ratings	% (tanθ)	18/20	17/21
			30-Minute Ratings	% (tanθ)	12/20	12/20
32	Total Weight	Without Battery	kg	2970	2970	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	5640	5810
			Rear	kg	710	820
34	No Load	Front	kg	1580	1750	
		Rear	kg	2270	2380	
35	Tires	Number	Front/Rear	2/2	2/2	
36	Size	Front		21X8-9-14PR (I)	21X8-9-14PR (I)	
37		Rear		18X7-8-14PR (I)	18X7-8-14PR (I)	
38	Wheelbase		mm	1500	1500	38
39	Tread	Front	mm	970	970	
		Rear	mm	940	940	
	Backrest Height		mm	1220	1220	
	Overhead Guard Clearance		mm	1035	1035	
	Counterweight Height		mm	1125	1135	
	Drawbar Height		mm	280	280	
	Step Height/Floor Height		mm	435/620	435/700	
40	Underclearance	Mast (Full Load)		mm	65	65
41		Center of Wheelbase (Full Load)		mm	85	85
		Drive Axle (Full Load)		mm	65	65
		Steer Axle (No Load)		mm	120	120
		Counterweight (No Load)		mm	115	115
		Minimum Under Clearance (Full Load)		mm	65(Mast)	65(Mast)
	Grade Clearance	Frame	% (tanθ)	25	25	
		Counterweight	% (tanθ)	49	49	
42	Brake	Service (Foot)		Hydraulic	Hydraulic	
43		Parking		Hand	Hand	
45	Battery	Voltage/Capacity (5-hour rating)	V/AH	48/565	48/730	
46		High	V/AH	48/600	-	
47	Weight (STD Capacity Type)		kg	880	1160	
48	Electric Motors	Drive		kW	10.7	10.7
		Load Handling		kW	12.2	12.2
		Energy Consumption According to VDI Cycle **		kWh/h	4.5	4.6
54	Control Type	Drive		Transistor inverter	Transistor inverter	
		Load Handling		Transistor inverter	Transistor inverter	
57	Operating Pressure	For Attachments	Mpa (psi)	14.7(2100)	14.7(2100)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB(A)	67	67	
	Vibration in accordance with in EN13059		m/s2	1.5	1.5	

NOTE: * Computed values.

** 60 VDI Work Cycles/h with Tested Load of 2500 kg

DIMENSIONAL DRAWINGS


Unit: mm
[] for 8FBH25



UNDERCLEARANCE

Mast (Full Load)	65
Center of Wheelbase (Full Load)	85
Drive Axle (Full Load)	65
Steer Axle (No Load)	120
Counterweight (No Load)	115
Minimum Under Clearance (No Load)	65(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	2500	2500	2500	2500	2300	1800
	600	2250	2250	2250	2250	2070	1620
	700	2050	2050	2050	2050	1890	1480
	800	1890	1890	1890	1890	1730	1360
	900	1740	1740	1740	1740	1600	1250
	1000	1620	1620	1620	1620	1490	1170
	1100	1520	1520	1520	1520	1390	1090
	1200	1420	1420	1420	1420	1310	1020
	1300	1340	1340	1340	1340	1230	960
	Dual Tire	500	2500	2500	2500	2500	2450
600		2250	2250	2250	2250	2210	2120
700		2050	2050	2050	2050	2010	1930
800		1890	1890	1890	1890	1850	1770
900		1740	1740	1740	1740	1710	1640
1000		1620	1620	1620	1620	1590	1520
1100		1520	1520	1520	1520	1490	1420
1200		1420	1420	1420	1420	1390	1340
1300		1340	1340	1340	1340	1310	1260

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	2400	2400	2300	2050	2050	1650	1000
	600	2170	2170	2080	1850	1850	1490	900
	700	1980	1980	1900	1690	1690	1360	820
	800	1820	1820	1750	1560	1560	1250	760
	900	1690	1690	1620	1440	1440	1160	700
	1000	1570	1570	1510	1340	1340	1080	650
	1100	1470	1470	1410	1260	1260	1010	610
	1200	1380	1380	1320	1180	1180	950	570
	1300	1300	1300	1250	1110	1110	890	540
	Dual Tire	500	2400	2400	2400	2300	2300	2200
600		2170	2170	2170	2080	2080	1990	1400
700		1980	1980	1980	1900	1900	1820	1280
800		1820	1820	1820	1750	1750	1670	1180
900		1690	1690	1690	1620	1620	1550	1090
1000		1570	1570	1570	1510	1510	1440	1010
1100		1470	1470	1470	1410	1410	1350	950
1200		1380	1380	1380	1320	1320	1270	890
1300		1300	1300	1300	1250	1250	1190	840

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered*	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual	
			Without Load Backrest	With Standard Load Backrest							deg
Wide Visible Mast (V)	2500	1725	3165	3720	130	130	7	11	2500	2500	
	2700	1825	3365	3920	130	130	7	11	2500	2500	
	3000	1975	3665	4220	130	130	7	11	2500	2500	
	3300	2125	3965	4520	130	130	7	11	2500	2500	
	3500	2225	4165	4720	130	130	7	11	2500	2500	
	3700	2385	4365	4920	130	130	7	11	2500	2500	
	4000	2575	4665	5220	130	130	7	5<11>	2500	2500	
	4500	2825	5165	5720	130	130	7	5	2300	2450	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3075	5665	6220	130	130	7	5	1800	2350	
	3000	1975	3600	4220	1375*	755*	7	11	2500	2500	
	3300	2125	3900	4520	1525*	905*	7	11	2500	2500	
	3500	2225	4100	4720	1625*	1005*	7	11	2500	2500	
	3700	2385	4300	4920	1785*	1165*	7	11	2500	2500	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2575	4600	5220	1975*	1355*	7	5<11>	2500	2500	
	3700	1775	4340	4920	1135*	555*	7	5	2400	2400	
	4000	1875	4640	5220	1235*	655*	7	5	2400	2400	
	4300	1975	4940	5520	1335*	755*	7	5	2300	2400	
	4500	2045	5140	5720	1405*	825*	7	5	2050	2300	
	4700	2125	5340	5920	1485*	905*	7	5	2050	2300	
	5000	2225	5640	6220	1585*	1005*	7	5	1650	2200	
	5500	2385	6140	6720	1745*	1165*	7	5	1250	2000	
6000	2575	6640	7220	1935*	1355*	7	5	1000	1550		

NOTE: Height of standard load backrest is 1220 mm.
* with optional tire sized 23x9-10-16PR, plus 20mm.
< > for dual tires.

The data in this publication was determined based on our standard testing condition. Operating performance may vary depending on the actual specification and condition of the vehicle as well as the condition of the operating area.

2,500 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	1	
2	Model			40-8FB25	2	
3	Load Capacity		kg	2500	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type		Front/Rear	Pneumatic	7	
8	Wheels (x = driven)		Front/Rear	2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	155	10	
13	Fork Size		L x W x T	1070/120/40	13	
	Fork Spread (Outside)		MAX./MIN.	1020/240		
14	Tilt Range		FWD/BWD	6/11	14	
15	Length to Fork Face		mm	2435	15	
16	Overall Width		mm	1230	16	
17	Mast Lowered Height		mm	1995	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height		mm	2160	19	
21	Turning Radius (Outside)		mm	2170	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	475	22	
	Rear Overhang		mm	310		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2640	23	
	Intersecting Aisle Width		mm	1915		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.5/14.5	24
			No Load	km/h	15.5/15.5	
		Lowering	Full Load	mm/sec	340	25
			No Load	mm/sec	600	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	12890/12010 (1310/1220)	27
			5-Minute Ratings	N (kg)	12890/12010 (1310/1220)	
			60-Minute Ratings	N (kg)	5200/5300 (530/540)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	20/24	29
			5-Minute Ratings	% (tanθ)	20/24	
			30-Minute Ratings	% (tanθ)	13/20	
32	Total Weight	Without Battery	kg	3010	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	6040	33
			Rear	kg	790	
34		No Load	Front	kg	2060	34
			Rear	kg	2270	
35		Number	Front/Rear	2/2	35	
36	Tires	Size	Front	7.00-12-12PR (I)	36	
37			Rear	6.00-9-10PR (I)	37	
38	Wheelbase		mm	1650	38	
39	Tread		Front	mm	960	39
			Rear	mm	965	
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1195		
	Drawbar Height			505		
	Step Height/Floor Height			490/755		
40	Underclearance	Mast (Full Load)		mm	75	40
41		Center of Wheelbase (Full Load)		mm	110	41
		Drive Axle (Full Load)		mm	115	
		Steer Axle (No Load)		mm	150	
		Counterweight (No Load)		mm	160	
		Minimum Under Clearance (Full Load)		mm	75(Mast)	
	Grade Clearance	Frame		% (tanθ)	29	
		Counterweight		% (tanθ)	96	
42	Brake	Service (Foot)			Hydraulic	42
43		Parking			Hand	43
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	48/845	45
			High	V/AH	-	
46	Weight (STD Capacity Type)		kg	1320	46	
47	Electric Motors	Drive		kW	10.7	47
48		Load Handling		kW	12.2	48
		Energy Consumption According to VDI Cycle **		kWh/h	4.6	
54	Control Type	Drive			Transistor inverter	54
		Load Handling			Transistor inverter	
57	Operating Pressure		For Attachments	Mpa (psi)	14.7 (2100)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)			dB(A)	-	
	Vibration in accordance with in EN13059			m/s2	-	

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 2500 kg.

DIMENSIONAL DRAWINGS


Unit: mm



UNDERCLEARANCE

Mast (Full Load)	75
Center of Wheelbase (Full Load)	110
Drive Axle (Full Load)	115
Steer Axle (No Load)	150
Counterweight (No Load)	160
Minimum Under Clearance (No Load)	75(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire	500	2500	2500	2500	2500	2500	2300	1800
	600	2260	2260	2260	2260	2260	2080	1630
	700	2070	2070	2070	2070	2070	1900	1490
	800	1910	1910	1910	1910	1910	1750	1370
	900	1770	1770	1770	1770	1770	1620	1270
	1000	1650	1650	1650	1650	1650	1510	1180
	1100	1540	1540	1540	1540	1540	1420	1110
	1200	1450	1450	1450	1450	1450	1330	1040
	1300	1370	1370	1370	1370	1370	1260	980
	Dual Tire	500	2500	2500	2500	2500	2500	2450
600		2260	2260	2260	2260	2260	2220	2130
700		2070	2070	2070	2070	2070	2030	1940
800		1910	1910	1910	1910	1910	1870	1790
900		1770	1770	1770	1770	1770	1730	1660
1000		1650	1650	1650	1650	1650	1610	1550
1100		1540	1540	1540	1540	1540	1510	1450
1200		1450	1450	1450	1450	1450	1420	1360
1300		1370	1370	1370	1370	1370	1340	1280

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	2400	2400	2300	2050	2050	1650	1250	1000
	600	2170	2170	2080	1860	1860	1490	1130	900
	700	1990	1990	1910	1700	1700	1370	1030	830
	800	1840	1840	1760	1570	1570	1260	950	760
	900	1700	1700	1630	1460	1460	1170	890	710
	1000	1590	1590	1520	1360	1360	1090	830	660
	1100	1490	1490	1430	1270	1270	1020	770	620
	1200	1400	1400	1340	1200	1200	960	730	580
	1300	1320	1320	1270	1130	1130	910	690	550
	Dual Tire	500	2400	2400	2400	2300	2300	2200	2000
600		2170	2170	2170	2080	2080	1990	1810	1400
700		1990	1990	1990	1910	1910	1830	1660	1280
800		1840	1840	1840	1760	1760	1680	1530	1180
900		1700	1700	1700	1630	1630	1560	1420	1100
1000		1590	1590	1590	1520	1520	1460	1320	1020
1100		1490	1490	1490	1430	1430	1360	1240	960
1200		1400	1400	1400	1340	1340	1280	1170	900
1300		1320	1320	1320	1270	1270	1210	1100	850

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	2500	1745	3150	3720	155	155	6	11	2500	2500
	2700	1845	3350	3920	155	155	6	11	2500	2500
	3000	1995	3650	4220	155	155	6	11	2500	2500
	3300	2145	3950	4520	155	155	6	11	2500	2500
	3500	2245	4150	4720	155	155	6	11	2500	2500
	3700	2405	4350	4920	155	155	6	11	2500	2500
	4000	2595	4650	5220	155	155	6	6<11>	2500	2500
	4500	2845	5150	5720	155	155	6	6	2300	2450
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3095	5650	6220	155	155	6	6	1800	2350
	3000	1995	3595	4220	1400	775	6	11	2500	2500
	3300	2145	3895	4520	1550	925	6	11	2500	2500
	3500	2245	4095	4720	1650	1025	6	11	2500	2500
	3700	2405	4295	4920	1810	1185	6	11	2500	2500
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2595	4595	5220	2000	1375	6	6<11>	2500	2500
	3700	1795	4265	4920	1230	575	6	6	2400	2400
	4000	1895	4565	5220	1330	675	6	6	2400	2400
	4300	1995	4865	5520	1430	775	6	6	2300	2400
	4500	2065	5065	5720	1500	845	6	6	2050	2300
	4700	2145	5265	5920	1580	925	6	6	2050	2300
	5000	2245	5565	6220	1680	1025	6	6	1650	2200
	5500	2405	6065	6720	1840	1185	6	6	1250	2000
6000	2595	6565	7220	2030	1375	6	6	1000	1550	

NOTE: Height of standard load backrest is 1220 mm.
<> for dual tires.

The data in this publication was determined based on our standard testing condition. Operating performance may vary depending on the actual specification and condition of the vehicle as well as the condition of the operating area.

3,000 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	1	
2	Model			8FB30	2	
3	Load Capacity		kg	3000	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type	Front/Rear		Pneumatic	7	
8	Wheels (x = driven)	Front/Rear		2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	135	10	
13	Fork Size	L x W x T	mm	1070/120/44	13	
	Fork Spread (Outside)	MAX./MIN.	mm	1070/240		
14	Tilt Range	FWD/BWD	deg	6/11	14	
15	Length to Fork Face		mm	2490	15	
16	Overall Width		mm	1240	16	
17	Mast Lowered Height		mm	2020	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height		mm	2195	19	
21	Turning Radius (Outside)		mm	2210	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	485	22	
	Rear Overhang		mm	355		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2695	23	
	Intersecting Aisle Width		mm	2005		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.0/14.0	24
			No Load	km/h	15.0/15.0	
		Lifting	Full Load	mm/sec	320	25
			No Load	mm/sec	550	
26	Lowering	Full Load	mm/sec	500	26	
		No Load	mm/sec	500		
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	13060/12630 (1330/1280)	27
			5-Minute Ratings	N (kg)	13060/12630 (1330/1280)	
			60-Minute Ratings	N (kg)	5300/5590 (540/570)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	17/22	29
			5-Minute Ratings	% (tanθ)	17/22	
			30-Minute Ratings	% (tanθ)	11/19	
32	Total Weight	Without Battery	kg	3690	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	6880	33
			Rear	kg	830	
34		No Load	Front	kg	2090	34
			Rear	kg	2620	
35	Tires	Number	Front/Rear	2/2	35	
36		Size	Front	28X9-15-14PR (I)	36	
37			Rear	6.50-10-10PR (I)	37	
38	Wheelbase		mm	1650	38	
39	Tread	Front	mm	1010	39	
		Rear	mm	965		
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1275		
	Drawbar Height			340		
	Step Height/Floor Height			515/785		
40	Underclearance	Mast (Full Load)	mm	115	40	
41		Center of Wheelbase (Full Load)	mm	140	41	
		Drive Axle (Full Load)	mm	155		
		Steer Axle (No Load)	mm	180		
		Counterweight (No Load)	mm	185		
		Minimum Under Clearance (Full Load)	mm	115(Mast)		
	Grade Clearance	Frame	% (tanθ)	36		
		Counterweight	% (tanθ)	95		
42	Brake	Service (Foot)		Hydraulic	42	
43		Parking			Hand	43
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	80/370	45
		High	V/AH	80/470		
46		Weight (STD Capacity Type)	kg	1020	46	
47	Electric Motors	Drive	kW	11.9	47	
48		Load Handling	kW	14.4	48	
		Energy Consumption According to VDI Cycle **	kWh/h	5.0	-	
54	Control Type	Drive		Transistor inverter	54	
		Load Handling		Transistor inverter		
57	Operating Pressure	For Attachments	Mpa (psi)	15.7 (2300)	57	
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)	69		
	Vibration in accordance with in EN13059		m/s2	1.5		

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 3000 kg.

DIMENSIONAL DRAWINGS


Unit: mm



UNDERCLEARANCE

Mast (Full Load)	115
Center of Wheelbase (Full Load)	140
Drive Axle (Full Load)	155
Steer Axle (No Load)	180
Counterweight (No Load)	185
Minimum Under Clearance (No Load)	115(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	3000	3000	3000	3000	2850	2350
	600	2720	2720	2720	2720	2580	2130
	700	2490	2490	2490	2490	2360	1950
	800	2290	2290	2290	2290	2180	1800
	900	2130	2130	2130	2130	2020	1670
	1000	1980	1980	1980	1980	1880	1550
	1100	1860	1860	1860	1860	1770	1450
	1200	1750	1750	1750	1750	1660	1370
	1300	1650	1650	1650	1650	1570	1290
	Dual Tire	500	3000	3000	3000	3000	3000
600		2720	2720	2720	2720	2720	2720
700		2490	2490	2490	2490	2490	2490
800		2290	2290	2290	2290	2290	2290
900		2130	2130	2130	2130	2130	2130
1000		1980	1980	1980	1980	1980	1980
1100		1860	1860	1860	1860	1860	1860
1200		1750	1750	1750	1750	1750	1750
1300		1650	1650	1650	1650	1650	1650

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	3000	3000	3000	2800	2800	2400	1450
	600	2720	2720	2720	2540	2540	2180	1310
	700	2490	2490	2490	2330	2330	1990	1200
	800	2300	2300	2300	2150	2150	1840	1110
	900	2130	2130	2130	1990	1990	1710	1030
	1000	1990	1990	1990	1860	1860	1590	960
	1100	1870	1870	1870	1740	1740	1490	900
	1200	1760	1760	1760	1640	1640	1400	850
	1300	1660	1660	1660	1550	1550	1320	800
	Dual Tire	500	3000	3000	3000	3000	3000	2900
600		2720	2720	2720	2720	2720	2630	1860
700		2490	2490	2490	2490	2490	2410	1700
800		2300	2300	2300	2300	2300	2220	1570
900		2130	2130	2130	2130	2130	2060	1460
1000		1990	1990	1990	1990	1990	1920	1360
1100		1870	1870	1870	1870	1870	1800	1270
1200		1760	1760	1760	1760	1760	1700	1200
1300		1660	1660	1660	1660	1660	1600	1130

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual	
			Without Load Backrest	With Standard Load Backrest							deg
Wide Visible Mast (V)	2500	1770	3220	3720	135	135	6	11	3000	3000	
	2700	1870	3420	3920	135	135	6	11	3000	3000	
	3000	2020	3720	4220	135	135	6	11	3000	3000	
	3300	2170	4020	4520	135	135	6	11	3000	3000	
	3500	2270	4220	4720	135	135	6	11	3000	3000	
	3700	2430	4420	4920	135	135	6	11	3000	3000	
	4000	2620	4720	5220	135	135	6	11	3000	3000	
	4500	2870	5220	5720	135	135	6	5	2850	3000	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3120	5720	6220	135	135	6	5	2350	3000	
	3000	2020	3615	4220	1405	800	6	11	3000	3000	
	3300	2170	3915	4520	1555	950	6	11	3000	3000	
	3500	2270	4115	4720	1655	1050	6	11	3000	3000	
	3700	2430	4315	4920	1815	1210	6	11	3000	3000	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2620	4615	5220	2005	1400	6	11	3000	3000	
	3700	1920	4315	4920	1305	700	6	5	3000	3000	
	4000	2020	4615	5220	1405	800	6	5	3000	3000	
	4300	2170	4915	5520	1555	950	6	5	3000	3000	
	4500	2220	5115	5720	1605	1000	6	5	2800	3000	
	4700	2270	5315	5920	1655	1050	6	5	2800	3000	
	5000	2430	5615	6220	1815	1210	6	5	2400	2900	
	5500	2620	6115	6720	2005	1400	6	5	1900	2650	
6000	2870	6615	7220	2255	1650	6	5	1450	2050		

NOTE: Height of standard load backrest is 1220 mm.

3,000 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	1	
2	Model			8FBH30	2	
3	Load Capacity		kg	3000	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type	Front/Rear		Pneumatic	7	
8	Wheels (x = driven)	Front/Rear		2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	135	10	
13	Fork Size	L x W x T	mm	1070/120/44	13	
	Fork Spread (Outside)	MAX./MIN.	mm	1070/240		
14	Tilt Range	FWD/BWD	deg	6/11	14	
15	Length to Fork Face		mm	2635	15	
16	Overall Width		mm	1240	16	
17	Mast Lowered Height		mm	2020	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height []:Height with Resin Roof		mm	2195 [2245]	19	
21	Turning Radius (Outside)		mm	2355	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	485	22	
	Rear Overhang		mm	355		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2840	23	
	Intersecting Aisle Width		mm	2070		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	14.0/14.0	24
			No Load	km/h	15.0/15.0	
		Lowering	Full Load	mm/sec	320	25
			No Load	mm/sec	550	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	500	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	12530/12610 (1270/1280)	27
			5-Minute Ratings	N (kg)	12530/12610 (1270/1280)	
			60-Minute Ratings	N (kg)	5040/5300 (510/540)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	16/25	29
			5-Minute Ratings	% (tanθ)	16/25	
			30-Minute Ratings	% (tanθ)	10/18	
32	Total Weight	Without Battery		kg	3365	32
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	7030	33
			Rear	kg	800	
34		No Load	Front	kg	2390	34
			Rear	kg	2440	
35		Number	Front/Rear		2/2	35
36	Tires		Front		28X9-15-14PR (I)	36
37		Size	Rear		6.50-10-10PR (I)	37
38	Wheelbase		mm		1805	38
39	Tread	Front	mm		1010	39
		Rear	mm		965	
	Backrest Height				1220	
	Overhead Guard Clearance				1035	
	Counterweight Height				1275	
	Drawbar Height				340	
	Step Height/Floor Height				515/785	
40	Underclearance	Mast (Full Load)	mm		115	40
41		Center of Wheelbase (Full Load)	mm		140	41
		Drive Axle (Full Load)	mm		155	
		Steer Axle (No Load)	mm		180	
		Counterweight (No Load)	mm		185	
		Minimum Under Clearance (Full Load)	mm		115(Mast)	
	Grade Clearance	Frame	% (tanθ)		36	
		Counterweight	% (tanθ)		95	
42	Brake	Service (Foot)			Hydraulic	42
43		Parking				Hand
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	80/565	45
		High		V/AH	-	
46		Weight (STD Capacity Type)	kg		1465	46
47	Electric Motors	Drive	kW		11.9	47
48		Load Handling	kW		14.4	48
		Energy Consumption According to VDI Cycle **	kWh/h		5.1	-
54	Control Type	Drive			Transistor inverter	54
		Load Handling				
57	Operating Pressure	For Attachments	Mpa (psi)		15.7 (2300)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)		69	
	Vibration in accordance with in EN13059		m/s2		1.5	


NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 3000 kg.

[] with Resin Roof

DIMENSIONAL DRAWINGS


Unit: mm
[] with Resin Roof



UNDERCLEARANCE

Mast (Full Load)	115
Center of Wheelbase (Full Load)	140
Drive Axle (Full Load)	155
Steer Axle (No Load)	180
Counterweight (No Load)	185
Minimum Under Clearance (No Load)	115(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire	500	3000	3000	3000	3000	3000	2850	2350
	600	2720	2720	2720	2720	2720	2580	2130
	700	2490	2490	2490	2490	2490	2360	1950
	800	2290	2290	2290	2290	2290	2180	1800
	900	2130	2130	2130	2130	2130	2020	1670
	1000	1980	1980	1980	1980	1980	1880	1550
	1100	1860	1860	1860	1860	1860	1770	1450
	1200	1750	1750	1750	1750	1750	1660	1370
	1300	1650	1650	1650	1650	1650	1570	1290
	Dual Tire	500	3000	3000	3000	3000	3000	3000
600		2720	2720	2720	2720	2720	2720	2720
700		2490	2490	2490	2490	2490	2490	2490
800		2290	2290	2290	2290	2290	2290	2290
900		2130	2130	2130	2130	2130	2130	2130
1000		1980	1980	1980	1980	1980	1980	1980
1100		1860	1860	1860	1860	1860	1860	1860
1200		1750	1750	1750	1750	1750	1750	1750
1300		1650	1650	1650	1650	1650	1650	1650

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	3000	3000	3000	2800	2800	2400	1900	1450
	600	2720	2720	2720	2540	2540	2180	1720	1310
	700	2490	2490	2490	2330	2330	1990	1580	1200
	800	2300	2300	2300	2150	2150	1840	1450	1110
	900	2130	2130	2130	1990	1990	1710	1350	1030
	1000	1990	1990	1990	1860	1860	1590	1260	960
	1100	1870	1870	1870	1740	1740	1490	1180	900
	1200	1760	1760	1760	1640	1640	1400	1110	850
	1300	1660	1660	1660	1550	1550	1320	1050	800
	Dual Tire	500	3000	3000	3000	3000	3000	2900	2650
600		2720	2720	2720	2720	2720	2630	2400	1860
700		2490	2490	2490	2490	2490	2420	2200	1700
800		2300	2300	2300	2300	2300	2220	2030	1570
900		2130	2130	2130	2130	2130	2060	1880	1460
1000		1990	1990	1990	1990	1990	1920	1760	1360
1100		1870	1870	1870	1870	1870	1800	1650	1270
1200		1760	1760	1760	1760	1760	1700	1550	1200
1300		1660	1660	1660	1660	1660	1600	1460	1130

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual	
			Without Load Backrest	With Standard Load Backrest							deg
Wide Visible Mast (V)	2500	1770	3220	3720	135	135	6	11	3000	3000	
	2700	1870	3420	3920	135	135	6	11	3000	3000	
	3000	2020	3720	4220	135	135	6	11	3000	3000	
	3300	2170	4020	4520	135	135	6	11	3000	3000	
	3500	2270	4220	4720	135	135	6	11	3000	3000	
	3700	2430	4420	4920	135	135	6	11	3000	3000	
	4000	2620	4720	5220	135	135	6	11	3000	3000	
	4500	2870	5220	5720	135	135	6	5	2850	3000	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3120	5720	6220	135	135	6	5	2350	3000	
	3000	2020	3615	4220	1405	800	6	11	3000	3000	
	3300	2170	3915	4520	1555	950	6	11	3000	3000	
	3500	2270	4115	4720	1655	1050	6	11	3000	3000	
	3700	2430	4315	4920	1815	1210	6	11	3000	3000	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2620	4615	5220	2005	1400	6	11	3000	3000	
	3700	1920	4315	4920	1305	700	6	5	3000	3000	
	4000	2020	4615	5220	1405	800	6	5	3000	3000	
	4300	2170	4915	5520	1555	950	6	5	3000	3000	
	4500	2220	5115	5720	1605	1000	6	5	2800	3000	
	4700	2270	5315	5920	1655	1050	6	5	2800	3000	
	5000	2430	5615	6220	1815	1210	6	5	2400	2900	
	5500	2620	6115	6720	2005	1400	6	5	1900	2650	
6000	2870	6615	7220	2255	1650	6	5	1450	2050		

NOTE: Height of standard load backrest is 1220 mm.

3,500 kg

MAIN VEHICLE SPECIFICATIONS


1	Manufacturer			TOYOTA	1	
2	Model			8FBJ35	2	
3	Load Capacity		kg	3500	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type		Front/Rear	Pneumatic	7	
8	Wheels (x = driven)		Front/Rear	2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	140	10	
13	Fork Size		L x W x T	1070/140/50	13	
	Fork Spread (Outside)		MAX./MIN.	1070/240		
14	Tilt Range		FWD/BWD	6/11	14	
15	Length to Fork Face		mm	2575	15	
16	Overall Width		mm	1240	16	
17	Mast Lowered Height		mm	2110	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height		mm	2195	19	
21	Turning Radius (Outside)		mm	2270	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	500	22	
	Rear Overhang		mm	425		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2770	23	
	Intersecting Aisle Width		mm	2045		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	13.0/13.0	24
			No Load	km/h	15.0/15.0	
		Lowering	Full Load	mm/sec	270	25
			No Load	mm/sec	460	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	450	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	12900/12550 (1310/1280)	27
			5-Minute Ratings	N (kg)	12900/12550 (1310/1280)	
			60-Minute Ratings	N (kg)	5100/5490 (520/560)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	14/20	29
			5-Minute Ratings	% (tanθ)	14/20	
			30-Minute Ratings	% (tanθ)	9/17	
32	Total Weight	Without Battery	kg	4290	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	7840	33
			Rear	kg	970	
34		No Load	Front	kg	2220	34
			Rear	kg	3090	
35	Tires	Number	Front/Rear	2/2	35	
36		Size	Front	28X9-15-14PR (I)	36	
37			Rear	6.50-10-14PR (I)	37	
38	Wheelbase		mm	1650	38	
39	Tread	Front	mm	1010	39	
		Rear	mm	965		
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1275		
	Drawbar Height			340		
	Step Height/Floor Height			515/785		
40	Underclearance	Mast (Full Load)		mm	115	40
41		Center of Wheelbase (Full Load)		mm	140	41
		Drive Axle (Full Load)		mm	155	
		Steer Axle (No Load)		mm	180	
		Counterweight (No Load)		mm	185	
		Minimum Under Clearance (Full Load)		mm	115(Mast)	
	Grade Clearance	Frame	% (tanθ)	36		
		Counterweight	% (tanθ)	66		
42	Brake	Service (Foot)		Hydraulic	42	
43		Parking		Hand	43	
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	80/370	45
		High	V/AH	80/470		
46	Weight (STD Capacity Type)		kg	1020	46	
47	Electric Motors	Drive	kW	11.9	47	
48		Load Handling	kW	14.4	48	
		Energy Consumption According to VDI Cycle **	kWh/h	5.5		
54	Control Type	Drive		Transistor inverter	54	
		Load Handling		Transistor inverter		
57	Operating Pressure	For Attachments	Mpa (psi)	15.7(2300)	57	
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)		dB (A)	69		
	Vibration in accordance with in EN13059		m/s2	1.5		

NOTE: * Computed values.

** 60 VDI circles/h with Tested Load of 3500 kg.

DIMENSIONAL DRAWINGS


Unit: mm



UNDERCLEARANCE

Mast (Full Load)	115
Center of Wheelbase (Full Load)	140
Drive Axle (Full Load)	155
Steer Axle (No Load)	180
Counterweight (No Load)	185
Minimum Under Clearance (No Load)	115(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3000	3300	3500	3700	4000	4500	5000
Single Tire	500	3500	3500	3500	3500	3500	2750
	600	3180	3180	3180	3180	3180	2490
	700	2910	2910	2910	2910	2910	2290
	800	2690	2690	2690	2690	2690	2110
	900	2490	2490	2490	2490	2490	1960
	1000	2330	2330	2330	2330	2330	1830
	1100	2180	2180	2180	2180	2180	1710
Dual Tire	1200	2050	2050	2050	2050	2050	1610
	1300	1940	1940	1940	1940	1940	1520
	500	3500	3500	3500	3500	3500	3400
	600	3180	3180	3180	3180	3180	3090
	700	2910	2910	2910	2910	2910	2830
	800	2690	2690	2690	2690	2690	2610
	900	2490	2490	2490	2490	2490	2420
1000	2330	2330	2330	2330	2330	2260	
1100	2180	2180	2180	2180	2180	2120	
1200	2050	2050	2050	2050	2050	1990	
1300	1940	1940	1940	1940	1940	1880	

FSV Mast (PN or PSC)

Unit: kg (W)

A (mm)	3700	4000	4300	4500	4700	5000	5500	6000
Single Tire	500	3500	3500	3500	2900	2900	2500	1500
	600	3180	3180	3180	2630	2630	2270	1360
	700	2920	2920	2920	2420	2420	2080	1250
	800	2690	2690	2690	2230	2230	1920	1150
	900	2500	2500	2500	2070	2070	1790	1070
	1000	2340	2340	2340	1930	1930	1670	1000
	1100	2190	2190	2190	1810	1810	1560	940
Dual Tire	1200	2060	2060	2060	1710	1710	1470	880
	1300	1950	1950	1950	1610	1610	1390	830
	500	3500	3500	3500	3400	3400	3300	2200
	600	3180	3180	3180	3090	3090	3000	2000
	700	2920	2920	2920	2830	2830	2750	1830
	800	2690	2690	2690	2620	2620	2540	1690
	900	2500	2500	2500	2430	2430	2360	1570
1000	2340	2340	2340	2270	2270	2200	1470	
1100	2190	2190	2190	2130	2130	2060	1370	
1200	2060	2060	2060	2000	2000	1940	1290	
1300	1950	1950	1950	1890	1890	1840	1220	

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height			Free Lift		Tilt Range		Load Capacity at 500 mm LC	
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single	Dual
			Without Load Backrest	With Standard Load Backrest						
Wide Visible Mast (V)	2500	1890	3360	3720	140	140	6	11	3500	3500
	2700	1990	3560	3920	140	140	6	11	3500	3500
	3000	2110	3860	4220	140	140	6	11	3500	3500
	3300	2290	4160	4520	140	140	6	11	3500	3500
	3500	2390	4360	4720	140	140	6	11	3500	3500
	3700	2490	4560	4920	140	140	6	11	3500	3500
	4000	2740	4860	5220	140	140	6	11	3500	3500
Wide Visible Full-Free Lift Two-Stage Mast (FV)	4500	2990	5360	5720	140	140	6	5	3350	3500
	5000	3240	5860	6220	140	140	6	5	2750	3400
	3000	2110	3725	4220	1385	890	6	11	3500	3500
	3300	2290	4025	4520	1565	1070	6	11	3500	3500
	3500	2390	4225	4720	1665	1170	6	11	3500	3500
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	3700	2490	4425	4920	1765	1270	6	11	3500	3500
	4000	2740	4725	5220	2015	1520	6	11	3500	3500
	3700	2020	4425	4920	1295	800	6	5	3500	3500
	4000	2170	4725	5220	1445	950	6	5	3500	3500
	4300	2225	5025	5520	1495	1005	6	5	3500	3500
	4500	2270	5225	5720	1545	1050	6	5	2900	3400
	4700	2430	5425	5920	1705	1210	6	5	2900	3400
5000	2620	5725	6220	1895	1400	6	5	2500	3300	
5500	2870	6225	6720	2145	1650	6	5	1950	2900	
6000	3120	6725	7220	2395	1900	6	5	1500	2200	

NOTE: Height of standard load backrest is 1220 mm.

3,500 kg

MAIN VEHICLE SPECIFICATIONS

1	Manufacturer			TOYOTA	1	
2	Model			8FBHJ35	2	
3	Load Capacity		kg	3500	3	
4	Load Center		mm	500	4	
5	Power Type			Battery	5	
6	Operator Position			Rider Seated	6	
7	Tire Type		Front/Rear	Pneumatic	7	
8	Wheels (x = driven)		Front/Rear	2x/2	8	
9	Maximum Fork Height (MFH)		mm	3000	9	
10	Free Lift		mm	140	10	
13	Fork Size		L x W x T	1070/140/50	13	
	Fork Spread (Outside)		MAX./MIN.	1070/240		
14	Tilt Range		FWD/BWD	6/11	14	
15	Length to Fork Face		mm	2660	15	
16	Overall Width		mm	1240	16	
17	Mast Lowered Height		mm	2110	17	
18	Mast Extended Height		mm	4220	18	
19	Overhead Guard Height []:Height with Resin Roof		mm	2195 [2245]	19	
21	Turning Radius (Outside)		mm	2365	21	
22	Load Distance (Centerline of front axle to front face of forks)		mm	500	22	
	Rear Overhang		mm	425		
23	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm	2865	23	
	Intersecting Aisle Width		mm	2080		
24	Speeds *	Travel, Max. (FWD/RVS)	Full Load	km/h	13.0/13.0	24
			No Load	km/h	15.0/15.0	
		Lowering	Full Load	mm/sec	270	25
			No Load	mm/sec	460	
26			Full Load	mm/sec	500	26
			No Load	mm/sec	450	
27	Drawbar Pull *	Full Load/ No Load	3-Minute Ratings	N (kg)	12380/12530 (1260/1270)	27
			5-Minute Ratings	N (kg)	12380/12530 (1260/1270)	
			60-Minute Ratings	N (kg)	4890/5210 (490/530)	
29	Gradeability *	Full Load/ No Load	3-Minute Ratings	% (tanθ)	14/24	29
			5-Minute Ratings	% (tanθ)	14/24	
			30-Minute Ratings	% (tanθ)	8/17	
32	Total Weight	Without Battery	kg	3945	32	
33	Weight Distribution (With STD Battery)	Full Load	Front	kg	7990	33
			Rear	kg	920	
34		No Load	Front	kg	2550	34
			Rear	kg	2860	
35		Number	Front/Rear		2/2	35
36	Tires	Size	Front		28X9-15-14PR (I)	36
37			Rear			6.50-10-14PR (I)
38	Wheelbase		mm	1805	38	
39	Tread	Front	mm	1010	39	
		Rear	mm	965		
	Backrest Height			1220		
	Overhead Guard Clearance			1035		
	Counterweight Height			1275		
	Drawbar Height			340		
	Step Height/Floor Height			515/785		
40	Underclearance	Mast (Full Load)		mm	115	40
41		Center of Wheelbase (Full Load)		mm	140	41
		Drive Axle (Full Load)		mm	155	
		Steer Axle (No Load)		mm	180	
		Counterweight (No Load)		mm	185	
		Minimum Under Clearance (Full Load)		mm	115(Mast)	
	Grade Clearance	Frame	% (tanθ)	36		
		Counterweight	% (tanθ)	66		
42	Brake	Service (Foot)			Hydraulic	42
43		Parking			Hand	43
45	Battery	Voltage/Capacity (5-hour rating)	STD	V/AH	80/565	45
46			High	V/AH	-	
47	Electric Motors	Weight (STD Capacity Type)		kg	1465	46
48		Drive		kW	11.9	47
		Load Handling		kW	14.4	48
	Energy Consumption According to VDI Cycle **		kWh/h	5.6		
54	Control Type	Drive			Transistor inverter	54
		Load Handling			Transistor inverter	
57	Operating Pressure		For Attachments	Mpa (psi)	15.7(2300)	57
	Sound level at the driver's ear according to EN12053 Uncertainty 4dB(A)			dB (A)	69	
	Vibration in accordance with in EN13059			m/s2	1.5	

NOTE: * Computed values.


** 60 VDI circles/h with Tested Load of 3500 kg.

[] with Resin Roof

DIMENSIONAL DRAWINGS

Unit: mm

[] with Resin Roof



UNDERCLEARANCE

Mast (Full Load)	115
Center of Wheelbase (Full Load)	140
Drive Axle (Full Load)	155
Steer Axle (No Load)	180
Counterweight (No Load)	185
Minimum Under Clearance (No Load)	115(Mast)

RATED CAPACITIES



A: Max. Fork Height
B: Load Center
W: Capacity

V, FV Mast

Unit: kg (W)

A (mm)		3000	3300	3500	3700	4000	4500	5000
Single Tire (PN)	500	3500	3450	3450	3450	3450	3300	2700
	600	3180	3130	3130	3130	3130	2990	2450
	700	2910	2870	2870	2870	2870	2740	2240
	800	2690	2650	2650	2650	2650	2530	2070
	900	2490	2460	2460	2460	2460	2350	1920
	1000	2330	2290	2290	2290	2290	2190	1790
	1100	2180	2150	2150	2150	2150	2060	1680
	1200	2050	2020	2020	2020	2020	1940	1580
	1300	1940	1910	1910	1910	1910	1830	1490
	Dual Tire (PN or PSC)	500	3500	3500	3500	3500	3500	3500
600		3180	3180	3180	3180	3180	3180	3090
700		2910	2910	2910	2910	2910	2910	2830
800		2690	2690	2690	2690	2690	2690	2610
900		2490	2490	2490	2490	2490	2490	2420
1000		2330	2330	2330	2330	2330	2330	2260
1100		2180	2180	2180	2180	2180	2180	2120
1200		2050	2050	2050	2050	2050	2050	1990
1300	1940	1940	1940	1940	1940	1940	1880	

FSV Mast

Unit: kg (W)

A (mm)		3700	4000	4300	4500	4700	5000	5500	6000
Single Tire (PN)	500	3450	3450	3450	2850	2850	2450	1900	1450
	600	3130	3130	3130	2590	2590	2220	1720	1310
	700	2870	2870	2870	2370	2370	2040	1580	1210
	800	2650	2650	2650	2190	2190	1880	1460	1110
	900	2470	2470	2470	2040	2040	1750	1360	1030
	1000	2300	2300	2300	1900	1900	1630	1270	960
	1100	2160	2160	2160	1780	1780	1530	1190	900
	1200	2030	2030	2030	1680	1680	1440	1120	850
	1300	1920	1920	1920	1580	1580	1360	1050	800
	Dual Tire (PN or PSC)	500	3500	3500	3500	3400	3400	3300	2900
600		3180	3180	3180	3090	3090	3000	2630	2000
700		2920	2920	2920	2830	2830	2750	2420	1830
800		2690	2690	2690	2620	2620	2540	2230	1690
900		2500	2500	2500	2430	2430	2360	2070	1570
1000		2340	2340	2340	2270	2270	2200	1930	1470
1100		2190	2190	2190	2130	2130	2060	1810	1370
1200		2060	2060	2060	2000	2000	1940	1710	1290
1300	1950	1950	1950	1890	1890	1840	1610	1220	

NOTE: For the rated capacity of Single Tire (PSC), please refer to the rated capacity chart of 8FBJ35.

MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Maximum Fork Height	Overall Height				Free Lift		Tilt Range		Load Capacity at 500 mm LC		
		Lowered	Extended		Without Load Backrest	With Standard Load Backrest	FWD	BWD	Single		Dual	
			Without Load Backrest	With Standard Load Backrest					PSC	PN		
	mm	mm	mm	mm	mm	mm	deg	deg	kg	kg	kg	
Wide Visible Mast (V)	2500	1890	3360	3720	140	140	6	11	3500	3500	3500	
	2700	1990	3560	3920	140	140	6	11	3500	3500	3500	
	3000	2110	3860	4220	140	140	6	11	3500	3500	3500	
	3300	2290	4160	4520	140	140	6	11	3500	3450	3500	
	3500	2390	4360	4720	140	140	6	11	3500	3450	3500	
	3700	2490	4560	4920	140	140	6	11	3500	3450	3500	
	4000	2740	4860	5220	140	140	6	11	3500	3450	3500	
	4500	2990	5360	5720	140	140	6	5	3350	3300	3500	
Wide Visible Full-Free Lift Two-Stage Mast (FV)	5000	3240	5860	6220	140	140	6	5	2750	2700	3400	
	3000	2110	3725	4220	1385	890	6	11	3500	3500	3500	
	3300	2290	4025	4520	1565	1070	6	11	3500	3450	3500	
	3500	2390	4225	4720	1665	1170	6	11	3500	3450	3500	
	3700	2490	4425	4920	1765	1270	6	11	3500	3450	3500	
Wide Visible Full-Free Lift Three-Stage Mast (FSV)	4000	2740	4725	5220	2015	1520	6	11	3500	3450	3500	
	3700	2020	4425	4920	1295	800	6	5	3500	3450	3500	
	4000	2170	4725	5220	1445	950	6	5	3500	3450	3500	
	4300	2225	5025	5520	1495	1005	6	5	3500	3450	3500	
	4500	2270	5225	5720	1545	1050	6	5	2900	2850	3400	
	4700	2430	5425	5920	1705	1210	6	5	2900	2850	3400	
	5000	2620	5725	6220	1895	1400	6	5	2500	2450	3300	
5500	2870	6225	6720	2145	1650	6	5	1950	1900	2900		
6000	3120	6725	7220	2395	1900	6	5	1500	1450	2200		

NOTE: Height of standard load backrest is 1220 mm.

The data in this publication was determined based on our standard testing condition. Operating performance may vary depending on the actual specification and condition of the vehicle as well as the condition of the operating area.

STANDARD EQUIPMENT

**8FB10.14.15.18.20.25.30.J35,
8FBH10.14.15.18.20.25.30.J35,
40-8FB15.20.25**

- Drive AC motor
- Load handling (Power Steering) AC motor
- Wide Visible Mast (V) [MFH: 3000 mm]
- Load backrest (Angled Lower Stay, V and FSV masts)
- Operator Presence Sensing System (OPS)
- Easy-down system (V mast)
- Multi-function display (Battery capacity indicator, Power-select function indicator, OPS indicator, Overheat warning, Low temperature warning, Parking brake warning indicator, Power meter, Battery overdischarge warning, Battery remaining-charge warning, Parking brake on/off alarm, Return-to-neutral warning, Digital diagnosis, Maximum speed limitation setting, Auto power off time setting)
- Power select function
- Power keep function
- Hour meter
- Auto power-off function
- Headlights
- Combination Lights
- ORS seat
- Memory tilt steering column
- Dual action parking brake
- Full hydraulic power steering
- Electric horn
- Emergency power shut-down button
- Battery connector handle
- Floor mat
- Assist grip
- Storage area
- Document crimp
- Overhead guard
- Overhead guard cap (8FB10-J35, 8FBH10-25, 40-8FB15-25)
- Resin roof (8FBH30. J35)

Availability and specifications are determined by market and are subject to change without notice.
Please consult your Toyota representative for details.

All rights reserved by Toyota Industries Corporation.



TOYOTA MATERIAL HANDLING INTERNATIONAL

S.S.8FB10-J35/E-2001/(S)/Printed in Japan/No.720760E0/500