

CNM-MSL-480T

SLIP LOADER



PRODUCT INFORMATION

Certification:



Engine brand	Yanmar 3TNV80
Rated power	20-25HP
Number of cylinders	3
Air intake way	Naturally Aspirated
Emissions standards	EURO5/EPA
Rated operating capacity	350Kg
Maximum operating capacity	480Kg
Maximum breakout force	5.5KN
Bucket capacity	0.12m ³
Driving speed	0-6km/h
Total cycling time	9s
System operating pressure	17-21bar
Fuel tank capacity	13L
Operating weight	1200KG
Track model	180*72*35

Vehicle height	1300mm
Length with standard bucket	2140mm
Vehicle width (standard tire)	1050mm
Length without standard bucket	1850mm
Bucket width	1050mm
Tail length	500mm
Height at maximum extension	2400mm
Height to the the bucket pin	1870mm
Maximum height as lay the bucket flat	1720mm
Dumping height	1510mm
Discharge distance	250mm
Track contact with ground length	900mm
Ground clearance	160mm
The flip angle of the bucket on the ground	27°
Bucket flip angle at highest position	114°

PRODUCT DETAIL

- 

It is equipped with the Yanmar 3TNV80 three-cylinder water-cooled engine, which has sufficient horse-power.
- 

Central control, easy to use and operate
- 

High-quality hydraulic cylinders, simple construction, reliable operation, no transmission clearance and smoothly
- 

Wear-resistant oil pipes and elastic rubber materials to ensure the elasticity of hydraulic cylinders
- 

LED lights have long service life and natural lighting effect
- 

We have multiple accessories, versatility, quick-change mountings

