

Diesel Water Pump – Fresh Pump



Model	DWP50	DWP80	DWP100
Suction / Discharger Port Diameter	50 (2")	80 (3")	100 (4")
Max flow rate (L/min)	600	833	1600
Rated total Head (m)	26	25	31
Max suction Head (m)	8.0	8.0	8.0
Engine Type	170F	178F	186F
Rotation speed (r/min)	3600	3600	3600
Max output (kW)	3.36	4.92	7.34
Cooling system	Forced air cooling by flywheel		
Ignition	Direct fuel injection		
Shaft rotation	Clockwise from flywheel end		
Starting System	Recoil Starter	Recoil Starter / Electric Starter	Recoil Starter / Electric Starter
Net Weight (kg)	30	44	60
Dimension (LxWxH)	555*460*510mm	610*530*560mm	680*550*650mm

Warranty Service:

- Three (3) months for the original invoice date
- Warranty is applied to products that have been, always, properly maintained and operated or used under normal operating conditions for which the product was designed.
- The manufacturer warrants this product due to defective materials or workmanship.

Suction Hose Kit



Discharge Hose Kit / Sunny Hose Kit



Wire Spring Hose



Item Code	Description	
HOSE-PSC/050	Wire Spring Hose 2" (50mm x 4mm x 30m)	
HOSE-PSC/075	Wire Spring Hose 3" (75mm x 5mm x 20m)	
HOSE-PSC/100	Wire Spring Hose 4" (100mm x 6mm x 20m)	

Sunny Hose



Item Code	Description	
HOSE-2DH2	2" Sunny Hose 2 Bar (91m / roll)	
HOSE-2DH3	3" Sunny Hose 2 Bar (91m / roll)	
HOSE-2DH4	4" Sunny Hose 2 Bar (91m / roll)	

Superior Clamp



Item Code	Description	
SC-91	Superior Clamp 85-91mm	
SC-97	Superior Clamp 91-97mm	
SC-104	Superior Clamp 97-104mm	
SC-112	Superior Clamp 104-112mm	

Foot Valve



Item Code	Description	
FV-2"	2" Foot Valve	
FV-3"	3" Foot Valve	
FV-4"	4" Foot Valve	

Camlock Fittings



Camlock Type A

Female Thread x Male Adaptor



Camlock Type C

Hose Shank x Female Coupler

Item Code	Description	
CAMLOCK-2F	2" Aluminium Camlock Female (Type C)	
CAMLOCK-2M	2" Aluminium Camlock Male (Type A)	
CAMLOCK-3F	3" Aluminium Camlock Female (Type C)	
CAMLOCK-3M	3" Aluminium Camlock Male (Type A)	
CAMLOCK-4F	4" Aluminium Camlock Female (Type C)	
CAMLOCK-4M	4" Aluminium Camlock Male (Type C)	