

HERCULES

9L FOAM Fire Extinguisher

Information

Foam fire extinguishers are suitable for putting out Class A and Class B fires. Upon discharge, it creates a barrier between the fuel and oxygen. This starves the fire and breaks the fire triangle. The cooling effect of foam will help to prevent reignition.

*These fire extinguishers have been dielectric tested, making them safe for use on electric fires at a minimum distance of 1m for up to 1000v.

Usage



Pull



Aim



Squeeze



Sweep

Before attempting to fight a fire, always ensure that you have an escape route. Fire fighting is a high risk activity, when in doubt, always choose to escape.

SPECIFICATIONS

SPECIFICATIONS	
Model	FT01-09A-00 CE1
Capacity	9L
Propellant	Nitrogen, Stored Pressure
Test Standard	SS EN3, BS EN3
Discharge Distance	Estimated > 3M
Discharge Time	≥ 15s
Body Diameter	185 MM
Total Height	585 MM
Total Weight	13.9 KG
Operating Temperature	5°C to 60°C
Pressure	15 Bar Working Pressure / 25 Bar Test Pressure
Fire Rating	21A 233B
Pack Dimension(mm)	190x190x610 (1 Per Box)
PART NO	FT01-09A-00 CE1



Fire Class



Class A



Class B



Electric

Under SCDF regulations, Singapore fire extinguishers cannot have Gas or Electric icons. SCDF recommends that the energy source be switched off before fire fighting.

Compliance



EN3



SG Fire Code



CE



Germany

Fully compliant to Singapore Fire Code and SCDF requirements. Comes with Certificate of Compliance and serial numbered labels for fire certificate.

Meticulously tested in both Singapore and Germany.

Accessories



Bracket Wall Mount 9L P/N: FEA-K-BRK-04 (Default option)