

HERCULES

6L

Wet Chemical Fire Extinguisher



Information

Wet Chemical Fire Extinguishers are effective against kitchen fires especially those involving deep fryers and grease.

To prevent splashing of the oil, these extinguishers are equipped with an applicator lance. This provides a degree of safety to the person operating the extinguisher.

*These fire extinguishers have been dielectric tested, making them safe for use on electric fires at a minimum distance of 1m for up to 1000v.

Usage



Pull



Aim



Squeeze



Sweep

Before attempting to fight a fire, always ensure that you have an escape route. Fire fighting is a high risk activity, when in doubt, always choose to escape.

WET CHEMICAL	
Model	FT01-06A (Rev 4) - 00
Capacity	6L
Propellant	Nitrogen, Stored Pressure
Test Standard	SS EN3, BS EN3
Discharge Distance	Estimated > 3M
Discharge Time	≥ 15s
Body Diameter	160 MM
Total Height	510 MM (Body) / 630 MM (Total)
Total Weight	10.1 KG
Operating Temp	5°C to 60°C
Pressure	15 Bar Working Pressure / 27 Bar Test Pressure
Fire Rating	13A 75F
Pack Dimension(mm)	170x170x535 (1 Per Box)
PART NO	FT01-06A (Rev 4) - 00

Fire Class



Class A



Class F



Electric

Under SCDF regulations, Singapore fire extinguishers cannot have Gas or Electric icons. SCDF recommends that the energy source be switched off before fire fighting.

Compliance



EN3



SG Fire Code



CE



Germany

Fully compliant to Singapore Fire Code and SCDF requirements. Comes with Certificate of Compliance and serial numbered labels for fire certificate.

Meticulously tested in both Singapore and Belgium.

Accessories



Bracket Wall Mount 6L P/N: FEA-K-BRK-04
(Default option)