



ENDRESS

Power Generators

ESE 606 HS-GT ES

Order No.: 112212

Alternator			synchron
Max. Output	1~	[kVA/kW]	6,4 / 6,4
Continuous Power	1~	[kVA/kW]	5,8 / 5,8
Nominal Voltage	1~	[V]	230
Nominal Current	1~	[A]	25,2
Power factor		cos ϕ	1,0
Frequency		[Hz]	50
Protection Class		[IP]	23

Engine

Engine Type			HONDA GX390 / 11 HP
Design			1-cycle 4-stroke OHV
Displacement		[cm ³]	389
Output 3000 rpm		[kW _m]	6,4
Fuel			petrol
Tank capacity		[l]	30
Consumption at 75% load		[l/h]	2,1
Running time at 75% load		[h]	14,3
Start-up system			electric starter, including battery
Sound power level LWA		[db(A)]	97
Sound pressure level LPA (7m)		[db(A)]	72
Weight in kg ca.			92
Dimensions L x W x H		[mm]	786 x 570 x 600
Shockproof sockets			2 x 230V 16A 1 x CEE 230V 32A

2018-3-7

Technical data and illustrations are not binding. We assume no liability for misprints.

ESE 606 HS-GT ES

Order No.: 112212



Does not conform to EU noise guideline 2000/14/EC

Equipment details

Large tank for long operation
Alternator overload protection
Tank level indicator
4-in-1 Display = V/Hz/h/low oil
Folding handles
AVR regulation
incl. Wheel set

Possible applications*

	230 V
Electric tools up to	4900 W
Gardening or construction equip. up to	3300 W
Compressors or pumps up to	2500 W

2018-3-7

Technical data and illustrations are not binding. We assume no liability for misprints.