

# HERCULES

## 2KG 5KG CARBON DIOXIDE Fire Extinguisher

### Information

Carbon Dioxide fire extinguishers are suitable for putting out Class B and electrical fires. Upon discharge, it displaces oxygen, cools and starves fires.

As carbon dioxide does not leave any residue upon discharge, it can be considered as a clean agent. It is a popular fire extinguisher for electrical and server rooms.

Subsequently, carbon dioxide does not conduct electricity, it will not cause electrical shocks from electric fires.

### Usage



Pull



Aim



Squeeze



Sweep

Before attempting to fight a fire, always ensure that you have an escape route. Fire fighting is a high risk activity, when in doubt, always choose to escape.

SPECIFICATIONS		
Model	FT02-02F-00	FT02-03D-00
Capacity	2KG	5KG
Propellant	Carbon Dioxide, Stored Pressure	
Test Standard	SS EN3, BS EN3	
Discharge Distance	Estimated 1M	
Discharge Time	≥ 6s	≥ 9s
Body Diameter	103 MM	135.8 MM
Total Height	565 MM	755 MM
Total Weight	6.4 KG	13.5 KG
Operating Temperature	-30°C to 60°C	
Pressure	56 Bar Working Pressure / 250 Bar Test Pressure	
Fire Rating	21B	89B
Pack Dimension(mm)	170x120x590	170x145x765
PART NO	FT02-02F-00	FT02-03D-00



### Fire Class



Class B



Electric

Under SCDF regulations, Singapore fire extinguishers cannot have Gas or Electric icons. SCDF recommends that the energy source be switched off before fire fighting.

### Compliance



EN3



SG Fire Code



CE



Germany

Fully compliant to Singapore Fire Code and SCDF requirements. Comes with Certificate of Compliance and serial numbered labels for fire certificate.

Meticulously tested in both Singapore and Germany.

### Accessories



L Bracket 2/5KG P/N: FEL-K-BRK03  
(Default option)