

***Smart Design, Smart Reliability
Smart Performance***




SMART MACHINE

**Diesel-Powered Forklift Trucks
2-3 ton**
(Counter-Balanced Type)

Smart Machine

MAIN FEATURES



Newly adopted engine "KUBOTA V2403"
clearing stringent environmental regulations.

New engine, compliant with global environmental regulations
New emission control and engine management system deliver excellent power, economy and reliability while meeting Euro stage IIIA, EPA interim Tier-4 and China 2nd stage regulations.

Design for convenient inspection and simple maintenance
All main components and parts are located on the same side which allows for easy maintenance.

Piston Displacement : 2434cc
Rated Horsepower : 36.5kW / 2600r.p.m.
Rated Torque : 158.6N·m / 1600r.p.m.

ENHANCED OPERATOR COMFORT



Expansive floor space for easier foot maneuvering
An amazing floor space by placing tilt cylinders under the floor. This gives a smooth footwell addition to easy entry and exit.



More convenient parking lever
The lever is positioned to the right of the steering wheel for easy entry and exit. A double-action brake release on the lever.




Easy entry and exit from an extra-wide-step
The secure step with enlarged foot space enables greater comfort and less fatigue while entering and exiting the vehicle.



Multifunctional suspension seat
Features include reinforced driver support, operator weight balance adjusting, reclining, and seat belt.

SUPERIOR MANEUVERABILITY AND ASSURED SAFETY



Innovative fork-landing mechanism
(Available for VM type mast) The fork-lowering speed decelerates at a height of approximately 150mm above the ground enabling accurate placement of the forks into the load fork pockets or pallet.



Reduced fatigue due to a semi-circular steering wheel
The A smaller diameter (300mm outer diameter) steering wheel gives improved vehicle maneuverability. In addition, this compact steering wheel makes it much easier to get on and off the truck.



High-mounted rear combination lights
The brake lights are easily visible at the top of the overhead guard. Recessed for protection, they are vibration resistant for long bulb life.



Single-piece headguard
The front and rear pillars as well as root are all welded together in a single-piece construction to give additional strength the entire structure.



Meter panel optimally located to the right of the driver's seat
The meter panel is located on the top right side of the dashboard for easier readability by the operator.



Anti-slip mat on the hood
A rubber strip is attached to the hood to prevent slippage while stepping on and off.



Meter panel with LED indicators
The LED has a longer life and is easy to read even during daylight shift operation.



Portable glove box



Cup holder

Smart Machine

SPECIFICATIONS / EQUIPMENT AND ACCESSORIES

STANDARD SPECIFICATIONS

Characteristics	1 Manufacturer				UNICARRIERS		
	2 Model				FD20T3KT	FD25T3KT	FD30T3KT
	3 Load Capacity			kg	2000	2500	3000
	4 Load Center			mm	500	500	500
	5 Power Type				Diesel		
	6 Operator Position				Seated		
	7 Tire Type				Pneumatic		
	8 Wheels (X=driven)			Front / Rear	2 × / 2		
Dimensions	9 Maximum Fork Height			mm	3000		
	10 Free Lift			mm	110		165
	13 Fork Size		L × W × T	mm	1070 × 122 × 40		1070 × 125 × 45
	Fork Spread (Outside)		Max. / Min.	mm	1020 / 245		1090 / 250
	14 Tilt Angle		Fwd / Bwd	deg	6 / 12		
	15 Length to Fork Face			mm	2485	2555	2705
	16 Overall Width			mm	1150		1225
	17 Mast Height Fork Lowered			mm	2030		2075
	18 Mast Height Fork Raised			mm	4030		4250
	19 Overhead Guard Height			mm	2070		2090
	20 Operator's Seat Height			mm	1045		1070
	21 Turning Radius (Outside)			mm	2170	2240	2400
	22 Load Distance(Centerline of front axle to front face of forks)			mm	450		480
	Rear Overhang			mm	435	505	525
	23 Basic Right Angle Stacking Aisle Width			mm	3890	3960	4150
Performance	24	Travel Max. (Fwd. / Rvs.)	Full Load	km/h	18.0		19.0
			No Load	km/h	18.5		19.5
			Full Load	mm/s	560		460
		Lifting	No Load	mm/s	600		490
			Full Load	mm/s	450		450
			No Load	mm/s	550		450
	25	Max. Drawbar Pull	Full Load	kN	16.7		14.7
			No Load	kN	8.3		9.8
30	Max. Gradeability*	Full Load	%	28	23	19	
		No Load	%	20	18	20	
Weight	32 Total Weight			kg	3240	3590	4160
	33 Weight Distribution	Full Load	Front	kg	4630	5360	6350
			Rear	kg	610	730	810
		No Load	Front	kg	1440	1370	1620
Rear			kg	1800	2220	2540	
Chassis & Wheels	35	Tires	Number	Front / Rear	2 / 2		
			Size	Front	7.00-12-12PR(I)		28x9-15-12PR(I)
		Rear	6.00-9-10PR(I)		6.50-10-10PR(I)		
	38 Wheelbase			mm	1600	1700	
	39 Tread		Front	mm	970	1000	
			Rear	mm	970	970	
	Backrest Height			mm	1000	1220	
	Overhead Guard Clearance			mm	1000		
	Counterweight Height			mm	1110	1130	
	Drawbar Pin Center Height			mm	530	560	
	Step Height / Floor Height			mm	435 / 655	460 / 680	
	Engine & Transmission	40 Underclearance	Min. with load		mm	110	140
Center of wheelbase			mm	140	165		
42 Brake		Service (Foot)			Hydraulic - Foot pedal		
		Parking			Mechanical - Hand lever		
45 Battery		Voltage / Capacity (5HR)		V/AH	12 / 55		
49 Internal Combustion Engine		Make / Model			KUBOTA V2403		
		Rated Hosepower / r.p.m.			36.5kW / 2600r.p.m. (49.6PS / 2600r.p.m.)		
	Rated Torque / r.p.m.			159N·m / 1600r.p.m. (16.2kgf·m / 1600r.p.m.)			
	Number of Cylinder			4			
	Piston Displacement		cc	2434			
	Alternator output		kW/Amp	0.48 / 40			
Fuel Tank Capacity			lit.	70			
55 Transmission	Type			Power-shift			
	Stage	Fwd. - Rvs.		1 - 1			
57 Operating Pressure	For Attachment		kg/cm2	180			

NOTE : *Computed Values

STANDARD EQUIPMENT AND ACCESSORIES

Equipment
Asbestos-free brake shoe materials
Donaldson dry type cyclopac air-cleaner
Radiator coolant reservoir
Cylinder type bonnet latch with locking function
Adjustable ORS seat with belt
Drawbar device
Engine auto glow system
Fuel water sedimenter
Full hydrostatic power steering
Durable overhead guard
Wide view 2-stage mast(VM300)
Hydraulic oil dipstick
ITA class II or class III carriage
J-lug pneumatic industrial tires
Lift circuit cut-off valve
Load backrest
Flow control valve
Return hydraulic filter
Suction hydraulic filter
Tilt lock valve
Transmission oil dipstick
Transmission oil filter
1070mm forks
2-spool control valve with pressure relief

Controls
Electric shift control lever
Lift and tilt levers
Multi-function switch lever with self-cancelling mechanism (Lighting & turn-signal)
Parking brake lever with inter-lock
Tilt adjustable steering post
Neutral safety mechanism

Accessories
Back-up buzzer
Back-up lights
Delux floor mat
Pen/Cup holder
Electric horn
Access-assisted hand grip
Front combination lights (turn signal, clearance)
Detachable and portable glove box
Head lights
High-mounted rear combination lights
Side view mirrors

Instruments and Switch
Charge indicator
Engine oil pressure warning indicator
Fuel gauge
Grow indicator
Hourmeter
Ignition key engine stop
Neutral safety switch
Fuel water sediment indicator
Water temperature gauge

NOTES :
Meets following major standards and code:
- ISO22915-2 Counter Balanced Lift Trucks, Stability & Safety Test (Int'l)
- JIS D6001 Industrial Lift Trucks (Japan)
- ISO D6011 Stability & Safety Test (Japan)
Overhead guard meets ISO 6055, JIS D6021

Wide View Mast VM

Mast Model	Rated Capacity 500mm load center(kg)				Max.	Overall Mast Height		Tilting Angle F/B deg	Service Weight(kg)					
	FD20T3KT		FD25T3KT		Fork Height mm	Lowered mm	Raised with Backrest mm		FD20T3KT			FD25T3KT		
	PNEUMATIC	UNIQUE(SE)	PNEUMATIC	UNIQUE(SE)					S	DD	SDD	S	DD	SDD
VM250	2000	2000	2500	2500	2500	1780	3530	6-10	3200	3305	3320	3550	3655	3670
VM270	2000	2000	2500	2500	2700	1880	3730	6-10	3215	3320	3335	3565	3670	3685
VM300	2000	2000	2500	2500	3000	2030	4030	6-12	3240	3345	3360	3590	3695	3710
VM330	2000	2000	2500	2500	3300	2180	4330	6-12	3265	3370	3385	3615	3720	3735
VM350	2000	2000	2500	2500	3500	2280	4530	6-12	3280	3385	3400	3630	3735	3750
VM375	2000	2000	2500	2500	3750	2405	4780	6-6 *6-12	3300	3405	3420	3650	3755	3770
VM400	2000	2000	2500	2500	4000	2580	5030	6-6 *6-12	3355	3460	3475	3705	3810	3825
VM425	1950 *2000	1950 *2000	2450 *2500	2450 *2500	4250	2705	5280	6-6 *6-12	3375	3480	3495	3725	3830	3845
VM450	1900 *1950	1900 *1950	2150 *2450	2350 *2450	4500	2830	5530	6-6 *6-12	3395	3500	3515	3745	3850	3865
VM475	1800 *1850	1800 *1850	1850 *2350	2200 *2350	4750	2955	5780	6-6	3415	3520	3535	3765	3870	3885
VM500	1650 *1700	1700	1700 *2250	2000 *2250	5000	3080	6030	6-6	3435	3540	3555	3785	3890	3905
VM550	*1500	*1500	*1700	*1700	5500	3380	6530	*3-6	—	3615	3630	—	3965	3980
VM600	*1300	*1300	*1400	*1400	6000	3630	7030	*3-6	—	3655	3670	—	4005	4020

Wide View Full Free 2-Stage Mast VFM

Mast Model	Rated Capacity 500mm load center(kg)				Max. Fork Height	Overall Mast Height		(2)Free lift with Backrest	Tilting Angle F/B	(3) Service Weight(kg)					
	FD20T3KT		FD25T3KT			Lowered	(1)Raised with Backrest			FD20T3KT			FD25T3KT		
	PNEUMATIC	UNIQUE(SE)	PNEUMATIC	UNIQUE(SE)						mm	mm	S	DD	SDD	S
VFM250	2000	2000	2500	2500	2500	1780	3530	780	6-10	3255	3360	3375	3605	3710	3725
VFM270	2000	2000	2500	2500	2700	1880	3730	880	6-10	3275	3380	3395	3625	3730	3745
VFM300	2000	2000	2500	2500	3000	2030	4030	1030	6-12	3300	3405	3420	3650	3755	3770
VFM330	2000	2000	2500	2500	3300	2180	4330	1180	6-12	3325	3430	3445	3675	3780	3795
VFM350	2000	2000	2500	2500	3500	2280	4530	1280	6-12	3340	3445	3460	3690	3795	3810
VFM375	2000	2000	2500	2500	3750	2405	4780	1405	6-6 *6-12	3360	3465	3480	3710	3815	3830
VFM400	2000	2000	2500	2500	4000	2580	5030	1580	6-6 *6-12	3420	3525	3540	3770	3875	3890
VFM425	1950 *2000	1950 *2000	2450 *2500	2450 *2500	4250	2705	5280	1705	6-6 *6-12	3440	3545	3560	3790	3895	3910
VFM450	1900 *1950	1900 *1950	2150 *2450	2350 *2450	4500	2830	5530	1830	6-6 *6-12	3465	3570	3585	3815	3920	3935
VFM475	1800 *1850	1800 *1850	1850 *2350	2200 *2350	4750	2955	5780	1955	6-6	3485	3590	3605	3835	3940	3955
VFM500	1650 *1700	1700	1700 *2250	2000 *2250	5000	3080	6030	2080	6-6	3505	3610	3625	3855	3960	4080

NOTE :(1) For height without backrest: -385mm
(2) For free lift without backrest: +385mm
(3) Weight for without backrest: -20kg

Wide View Full Free 3-Stage Mast VFHM

Mast Model	Rated Capacity 500mm load center(kg)				Max. Fork Height mm	Overall Mast Height		(2)Free lift with Backrest mm	Tilting Angle F/B deg	(3) Service Weight(kg)					
	FD20T3KT		FD25T3KT			Lowered mm	(1)Raised with Backrest mm			FD20T3KT			FD25T3KT		
	PNEUMATIC	UNIQUE(SE)	PNEUMATIC	UNIQUE(SE)						S	DD	SDD	S	DD	SDD
VFHM360	2000	2000	2500	2500	3600	1780	4630	780	6-6 *6-10	3395	3500	3515	3745	3850	3865
VFHM400	2000	2000	2500	2500	4000	1905	5030	905	6-6 *6-10	3425	3530	3545	3775	3880	3895
VFHM435	1900 *2000	1900 *2000	2200 *2400	2300 *2400	4350	2030	5380	1030	6-6 *6-10	3455	3560	3575	3805	3910	3925
VFHM480	1700 *1900	1800 *1900	1900 *2300	2200 *2300	4800	2180	5830	1180	6-6 *6-10	3485	3590	3605	3835	3940	3955
VFHM500	1500 *1800	1750 *1800	1600 *2250	2000 *2250	5000	2280	6030	1280	6-6 *6-10	3510	3615	3630	3860	3965	3980
VFHM540	1200 *1750	1650 *1750	1300 *2150	1700 *2150	5400	2405	6430	1405	3-6	3540	3645	3660	3890	3995	4010
VFHM600	900 *1650	1100 *1650	950 *1800	1100 *1800	6000	2630	7030	1630	3-6	3635	3740	3755	3985	4090	4105

NOTE :(1) For height without backrest: -455mm
(2) For free lift without backrest: +455mm
(3) Weight for without backrest: -20kg

NOTE :

Rated capacity with (*): Shows capacity with DD: front dual tires.
Service weight of VM550-600 represents the weight of vehicles equipped with "SDD:special dual tires".
Lifting speed with VFM/VFHM mast: with VFM 480mm/s with load. 530mm/s without load.
with VFHM 500mm/s with load. 550mm/s without load.
Lowering speed with VFM/VFHM mast: 400mm/s with load. 350mm/s without load.
Overall vehicle length with VFHM mast: +15mm longer than of standard model with VM/VFM mast.

Wide View Mast VM

Mast Model	Rated Capacity 500mm load center(kg)		Max. Fork Height	Overall Mast Height		Tilting Angle F/B	Service Weight(kg)		
	FD30T3KT			Lowered	Raised with Backrest		FD30T3KT		
	PNEUMATIC	UNIQUE(SE)					mm	mm	mm
VM250	3000	3000	2500	1825	3750	6-10	4120	4155	4270
VM270	3000	3000	2700	1925	3950	6-10	4135	4170	4285
VM300	3000	3000	3000	2075	4250	6-12	4160	4195	4310
VM330	3000	3000	3300	2225	4550	6-12	4185	4220	4335
VM350	3000	3000	3500	2325	4750	6-12	4200	4235	4350
VM375	3000	3000	3750	2450	5000	6-6 *6-12	4220	4255	4370
VM400	3000	3000	4000	2625	5250	6-6 *6-12	4280	4315	4430
VM425	2900 *3000	3000	4250	2750	5500	6-6 *6-12	4300	4335	4450
VM450	2800 *3000	3000	4500	2875	5750	6-6 *6-12	4320	4355	4470
VM475	2750 *2900	2900	4750	3000	6000	6-6	4340	4375	4490
VM500	2700 *2850	2850	5000	3125	6250	6-6	4365	4400	4515
VM550	*2400	*2400	5500	3425	6750	*3-6	—	4475	4590
VM600	*2000	*2000	6000	3675	7250	*3-6	—	4515	4630

Wide View Full Free 2-Stage Mast VFM

Mast Model	Rated Capacity 500mm load center(kg)		Max. Fork Height	Overall Mast Height		(2)Free lift with Backrest	Tilting Angle F/B	(3) Service Weight(kg)		
	FD30T3KT			Lowered	(1)Raised with Backrest			FD30T3KT		
	PNEUMATIC	UNIQUE(SE)						mm	mm	mm
VFM250	3000	3000	2500	1825	3750	600	6-10	4160	4195	4310
VFM270	3000	3000	2700	1925	3950	700	6-10	4175	4210	4325
VFM300	3000	3000	3000	2075	4250	850	6-12	4205	4240	4355
VFM330	3000	3000	3300	2225	4550	1000	6-12	4230	4265	4380
VFM350	3000	3000	3500	2325	4750	1100	6-12	4245	4280	4395
VFM375	3000	3000	3750	2450	5000	1225	6-6 *6-12	4270	4305	4420
VFM400	3000	3000	4000	2625	5250	1400	6-6 *6-12	4335	4370	4485
VFM425	2900 *3000	3000	4250	2750	5500	1525	6-6 *6-12	4355	4390	4505
VFM450	2800 *3000	3000	4500	2875	5750	1650	6-6 *6-12	4375	4410	4525
VFM475	2750 *2900	2900	4750	3000	6000	1775	6-6	4400	4435	4550
VFM500	2700 *2850	2850	5000	3125	6250	1900	6-6	4420	4455	4570

NOTE :(1) For height without backrest: -520mm
(2) For free lift without backrest: +520mm
(3) Weight for without backrest: -30kg

Wide View Full Free 3-Stage Mast VFHM

Mast Model	Rated Capacity 500mm load center(kg)		Max. Fork Height mm	Overall Mast Height		(2)Free lift with Backrest mm	Tilting Angle F/B deg	(3) Service Weight(kg)		
	FD30T3KT			Lowered mm	(1)Raised with Backrest mm			FD30T3KT		
	PNEUMATIC	UNIQUE(SE)						S	DD	SDD
VFHM360	3000	3000	3600	1825	4860	600	6-6 *6-10	4305	4340	4455
VFHM400	3000	3000	4000	1950	5260	725	6-6 *6-10	4335	4370	4485
VFHM435	2900 *3000	2900 *3000	4350	2075	5610	850	6-6 *6-10	4370	4405	4520
VFHM480	2800 *2900	2800 *2900	4800	2225	6060	1000	6-6 *6-10	4405	4440	4555
VFHM500	2600 *2750	2750	5000	2325	6260	1100	6-6 *6-10	4430	4465	4580
VFHM540	1900 *2650	2500 *2650	5400	2450	6660	1225	3-6	4465	4500	4615
VFHM600	1400 *2100	1850 *2100	6000	2675	7260	1450	3-6	4560	4595	4710

NOTE :(1) For height without backrest: -580mm
(2) For free lift without backrest: +580mm
(3) Weight for without backrest: -30kg


NOTE :

Rated capacity with (*): Shows capacity with DD: front dual tires.
Service weight of VM550-600 represents the weight of vehicles equipped with "SDD:special dual tires".
Lifting speed with VFM/VFHM mast: with VFM 410mm/s with load. 440mm/s without load.
with VFHM 420mm/s with load. 460mm/s without load.
Lowering speed with VFM/VFHM mast: 400mm/s with load. 350mm/s without load.
Overall vehicle length with VFHM mast: +15mm longer than of standard model with VM/VFM mast.

Smart Machine
OPTIONAL EQUIPMENT

Name		Att. code	FD20T3KT	FD25T3KT	FD30T3KT	Ref.
High and low mast		VM	○	○	○	
Full-free mast		VFM	○	○	○	
Full free 3-stage mast		VFHM	○	○	○	
Long fork		LF	○	○	○	
Wide finger bar		WF	○	○	○	
High load backrest		HBR	○	○	○	
Tire	Double	DD	○	○	○	
	Special double	SDD	○	○	○	
	U-lug	T	○	○	○	
	J-lug steel breaker	TJS	○	○	—	
	Snow	TS	○	○	○	
	Unique tire	TU	○	○	○	
Colored tire(White, Green)		TUW(G)	○	○	○	
Double-element air cleaner		ADE	○	○	○	
Plate-fin radiator		RADPF	○	○	○	
Spark prevention muffler		CBM	○	○	○	
Exhaust purification muffler		EPM	○	○	○	Two-way catalyst type
Diffusion exhaust muffler		DTP	○	○	○	
Upright muffler		TUE	○	○	○	
Front windshield (with wiper)		AWO71	○	○	○	
Small fan		FAN	○	○	○	
Rear work light		RWL	○	○	○	
Beacon light (Yellow/Red)		RLY/RLR	○	○	○	
Beacon light, interlocked with back-up alarm		BBR	○	○	○	
Spot light		SPL	○	○	○	
Lamps mounted on mast		HL	○	○	○	
Lamp guard		HLG	○	○	○	
Harbor specification head lamp BKT		BKH	○	○	○	
Center rearview mirror		BMC	○	○	○	
Back-up buzzer (with volume control)		BBA	○	○	○	
Back-up sound alarm		BBV	○	○	○	
Speedometer		SM	○	○	○	
Ammeter		AM	○	○	○	
Torque converter oil temp. gauge		TTM	○	○	○	
Reverse arrangement of shift lever		LCR	○	○	○	
Left-side arrangement of parking lever		PLR	○	○	○	
Guitar-shaped key switch		SWD	○	○	○	
Tilt cylinder boot		TLB	○	○	○	
Tilt gauge		TG	○	○	○	
Detachable counterweight		HC	○	○	○	Simplified type
Tool kit		TO	○	○	○	
Tool box		TOB	○	○	○	
Fire extinguisher		FE	○	○	○	
Battery for cold region		WS	○	○	○	
3-throw valve		3SV	○	○	○	
4-throw valve		4SV	○	○	○	
3-throw VM piping		AP3	○	○	○	
4-throw VM piping		AP4	○	○	○	
3-throw VFM/VFHM piping		AR3	○	○	○	
4-throw VFM/VFHM piping		AR4	○	○	○	
4-way detachable piping		4DK	○	○	○	
Variable relief valve		VRV	○	○	○	
Oil-filled lift cylinders		RTL	○	○	○	
Quick release device		ATR	○	○	○	Hook type
Power steering cylinder boot		PSB	○	○	○	
Licence plate with lamp		LPL	○	○	○	
Low-noise kit forks & carriage		SMS	○	○	○	
Rear working light linked with traveling backward		BBW	○	○	○	
Head guard canvas		HGC	○	○	○	

NOTE : ○:Available, — :Not available



STANDARD DIMENSIONS

Model	FD20T3KT	FD25T3KT	FD30T3KT
	mm	mm	mm
① Overall height, fork raised(with backrest)	4030	4030	4250
② Maximum fork height	3000	3000	3000
③ Mast height, fork lowered	2030	2030	2075
④ Backrest height	1000	1000	1220
⑤ Free lift	110	110	165
⑥ Fork thickness	40	40	45
⑦ Minimum ground clearance	110	110	140
⑧ Overall length(with forks)	3555	3625	3775
⑨ Overall length(without forks)	2485	2555	2705
⑩ Fork length	1070	1070	1070
⑪ Load distance	450	450	480
⑫ Wheelbase	1600	1600	1700
⑬ Rear overhang	435	505	525
⑭ Drawbar pin center height	530	530	560
⑮ Overhead guard clearance(from face of seat)	1000	1000	1000
⑯ Overall height(overhead guard)	2070	2070	2090
⑰ Overall width	1150	1150	1225
⑱ Fork spread(outside)	245-1020	245-1020	250-1090
⑲ Tread (front)	970	970	1000
⑳ Tread (rear)	970	970	970
㉑ Fork width	122	122	125
㉒ Inside turning radius	160	160	200
㉓ Outside turning radius	2170	2240	2400
㉔ Minimum intersecting aisle	2210	2230	2330
㉕ Tilt angles(forward-backward)	6-12 deg.	6-12 deg.	6-12 deg.

DIMENSIONS WITH FRONT DUAL DRIVE WHEELS(option)

Model	FD20T3KT	FD25T3KT	FD30T3KT
Tire size (front dual Type: DD)	4 × 5.50-15-8PR(I)		4 × 6.00-15-10PR(I)
	mm	mm	mm
⑰ Overall width	1480	1480	1520
⑲ Tread (front)	1130	1130	1170
㉒ Inside turning radius	100	100	100
㉓ Outside turning radius	2240	2310	2430
㉔ Minimum intersecting aisle	2320	2340	2445

Tire size (front dual Type: SDD)	4 × 7.00-12-12PR(I)		4 × 28 × 9 - 15-12PR(I)
	mm	mm	mm
⑰ Overall width	1590	1590	1750
⑲ Tread (front)	1190	1190	1260
㉒ Inside turning radius	100	100	100
㉓ Outside turning radius	2280	2350	2500
㉔ Minimum intersecting aisle	2370	2380	2490



- UniCarriers Corporation retains the right to change these products and specifications without incurring any obligation relating to such changes.
- These products and specifications are subject to change without notice.
- Photos and illustrations may or may not include optional equipment and accessories.
- Features and specifications may vary depending on markets.
- Performance data and dimensions are nominal and subject to tolerances.
- Produced in ISO certified factory.