



HIFOUNE

NEW C SERIES I.C. FORKLIFT

FD 30

Specification

Model	FD30		
Specifications	-	Power Unit	Diesel
	-	Operator Type	Driver/Seat
	-	Transmission Box Type	Automatic
	kg	Load Capacity	3000
	mm	Load Center	500
	mm	Max Lifting Height	3000
	-	Tire Type	Pneumatic Tire
	-	Front Tire Number	2
	-	Rear Tire Number	2
	-	Front Tire Size	28x9-15-14PR
-	Rear Tire Size	6.5-10-10PR	
Performance	mm/s	Lifting Speed (Loaded)	630
	mm/s	Lifting Speed (Unloaded)	690
	mm/s	Lowering Speed (Loaded)	480
	mm/s	Lowering Speed (Unloaded)	450
	km/h	Travelling Speed (Loaded)	17
	km/h	Travelling Speed (Unloaded)	19
	%	Max Grade-ability (Loaded)	21
	kN	Max Drawbar Pull (Loaded)	18
	deg	Mast Tilting Angle (Fwd/Bwd)	6/12
	Dimensions	mm	Free Lifting Height
mm		Turning Radius	2400
mm		Overall Length (without fork)	2705
mm		Overall Width	1240
mm		Overhead Guard Height	2100
mm		Fork Size (LxWxT)	1070x125x45
mm		Mast Height (Fork Lowered)	2140
V/Ah		Battery (Voltage/Capacity)	12/90
kg		Truck Weight	4380
L		Fuel Tank Capacity	70
Engine	-	Brand	MITSUBISHI
	-	Model	S4S
	kw/rpm	Rated Power	34.4/2250
	n-m/rpm	Rated Torque	169/1700
	-	Number of Cylinder	4
-	Displacement	3.33	

The standard model data would vary according to the configuration.

