

SPECIFICATIONS

| MODELS | T14JE-2 | | T16JE-2 | | T18JE-2 | | T20JE-2 | |
|----------------------------------|-----------------------------------|------------|-----------|------------|-----------------------------------|------------|-----------|------------|
| | Metric | Imperial | Metric | Imperial | Metric | Imperial | Metric | Imperial |
| Measurements | | | | | | | | |
| Work Height Max. | 16.3m | 53'6" | 18.3m | 60' | 20.6m | 67'7" | 22m | 72'2" |
| Platform Height Max. | 14.3m | 46'11" | 16.3m | 53'6" | 18.6m | 61' | 20m | 65'7" |
| Horizontal Outreach | 9.06m | 29'9" | 11.3m | 37'1" | 12.74m | 41'10" | 13.62m | 44'8" |
| Platform Length | 2.44m | 8' | 2.44m | 8' | 2.44m | 8' | 2.44m | 8' |
| Platform Width | 0.9m | 2'11" | 0.9m | 2'11" | 0.9m | 2'11" | 0.9m | 2'11" |
| A Stowed Length | 7.94m | 26'1" | 9.18m | 30'1" | 10.09m | 33'1" | 10.69m | 35'1" |
| Length-Transport (jib tucked) | 5.65m | 18'6" | 6.87m | 22'6" | 7.79m | 25'7" | 8.38m | 27'6" |
| B Overall Width | 2.42m | 7'11" | 2.42m | 7'11" | 2.5m | 8'2" | 2.5m | 8'2" |
| C Stowed Height | 2.65m | 8'8" | 2.65m | 8'8" | 2.62m | 8'7" | 2.68m | 8'10" |
| Height-Transport | 3.1m | 10'2" | 3.02m | 9'11" | 3.06m | 10' | 3m | 9'10" |
| D Wheelbase | 2.4m | 7'10" | 2.4m | 7'10" | 2.51m | 8'3" | 2.51m | 8'3" |
| E Ground Clearance | 0.37m | 1'3" | 0.37m | 1'3" | 0.37m | 1'3" | 0.4m | 1'4" |
| PRODUCTIVITY | | | | | | | | |
| Platform Capacity (unrestricted) | 300kg | 661 lbs | 300kg | 661 lbs | 300kg | 661 lbs | 300kg | 661 lbs |
| Platform Capacity (restricted) | 450kg | 992 lbs | 450kg | 992 lbs | 450kg | 992 lbs | 450kg | 992 lbs |
| Max. Platform Occupancy | 2 (unrestricted) / 3 (restricted) | | | | 2 (unrestricted) / 3 (restricted) | | | |
| Turntable Rotation | 360° | 360° | 360° | 360° | 360° | 360° | 360° | 360° |
| Drive Speed-Stowed | 5km/h | 3.1mph | 5km/h | 3.1mph | 5km/h | 3.1mph | 5km/h | 3.1mph |
| Drive Speed-Raised | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph |
| Gradeability | 45% | 45% | 45% | 45% | 45% | 45% | 45% | 45% |
| Max. Wind Speed | 12.5m/s | 28mph | 12.5m/s | 28mph | 12.5m/s | 28mph | 12.5m/s | 28mph |
| Turning Radius-Inside | 3m | 9'10" | 3m | 9'10" | 3.15m | 10'4" | 3.5m | 11'6" |
| Turning Radius-Outside | 5.8m | 19' | 5.8m | 19' | 6.2m | 20'4" | 6.35m | 20'10" |
| Max. Slope | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° |
| Tire Type | Solid | | Solid | | Solid | | Solid | |
| Tire Models | 33x12-20 | | 33x12-20 | | 33x12-20 | | 36x14-20 | |
| Ground Pressure, Tyres | 517 kPa | 75 psi | 572 kPa | 83 psi | 695.2 kPa | 100.8 psi | 605 kPa | 87.8 psi |
| POWER | | | | | | | | |
| Lithium Battery | 80V 125Ah | | 80V 125Ah | | 80V 173Ah | | 80V 228Ah | |
| HYDRAULIC SYSTEM | | | | | | | | |
| Hydraulic Oil Volume | 80L | 21.1gal | 80L | 21.1gal | 90L | 23.8gal | 90L | 23.8gal |
| WEIGHT | | | | | | | | |
| Machine Weight | 6,700kg | 14,771 lbs | 7,400kg | 16,314 lbs | 8,300kg | 18,298 lbs | 9,400kg | 20,723 lbs |

SPECIFICATIONS

| MODELS | T22JE-2 | | T26JE-2 | | T28JE-2 | | T32JE-2 | |
|----------------------------------|-----------------------------------|------------|-------------|------------|-----------------------------------|------------|-------------|------------|
| | Metric | Imperial | Metric | Imperial | Metric | Imperial | Metric | Imperial |
| Measurements | | | | | | | | |
| Work Height Max. | 24.2m | 79'5" | 28.2m | 92'6" | 30.2m | 99'1" | 34m | 111'7" |
| Platform Height Max. | 22.2m | 72'10" | 26.2m | 85'11" | 28.2m | 92'6" | 32m | 105' |
| Horizontal Outreach | 15.47m | 50'9" | 20m | 65'7" | 21.42m | 70'3" | 19.24m | 63'1" |
| Platform Length | 2.44m | 8' | 2.44m | 8' | 2.44m | 8' | 2.44m | 8' |
| Platform Width | 0.9m | 2'11" | 0.9m | 2'11" | 0.9m | 2'11" | 0.9m | 2'11" |
| A Stowed Length | 9.86m | 32'4" | 11.62m | 38'1" | 12.63m | 41'5" | 13.06m | 42'10" |
| Length-Transport (jib tucked) | 7.56m | 24'10" | 9.41m | 30'10" | 10.36m | 34' | 10.79m | 35'5" |
| B Overall Width | 2.5m | 8'2" | 2.5m | 8'2" | 2.5m | 8'2" | 2.5m | 8'2" |
| C Stowed Height | 2.76m | 9'1" | 2.83m | 9'3" | 2.83m | 9'3" | 2.83m | 9'3" |
| Height-Transport | 3m | 9'10" | 3.1m | 10'2" | 3.13m | 10'3" | 3.1m | 10'2" |
| D Wheelbase | 2.51m | 8'3" | 2.85m | 9'4" | 2.85m | 9'4" | 3.05m | 10' |
| E Ground Clearance | 0.4m | 1'4" | 0.4m | 1'4" | 0.4m | 1'4" | 0.44m | 1'5" |
| PRODUCTIVITY | | | | | | | | |
| Platform Capacity (unrestricted) | 300kg | 661 lbs | 300kg | 661 lbs | 300kg | 661 lbs | 300kg | 661 lbs |
| Platform Capacity (restricted) | 450kg | 992 lbs | 450kg | 992 lbs | 450kg | 992 lbs | 450kg | 992 lbs |
| Max. Platform Occupancy | 2 (unrestricted) / 3 (restricted) | | | | 2 (unrestricted) / 3 (restricted) | | | |
| Turntable Rotation | 360° | 360° | 360° | 360° | 360° | 360° | 360° | 360° |
| Drive Speed-Stowed | 5km/h | 3.1mph | 5km/h | 3.1mph | 5km/h | 3.1mph | 5km/h | 3.1mph |
| Drive Speed-Raised | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph | 0.6km/h | 0.37mph |
| Gradeability | 45% | 45% | 45% | 45% | 45% | 45% | 35% | 35% |
| Max. Wind Speed | 12.5m/s | 28mph | 12.5m/s | 28mph | 12.5m/s | 28mph | 12.5m/s | 28mph |
| Turning Radius-Inside | 3.5m | 11'6" | 4m | 13'1" | 4m | 13'1" | 4.68m | 15'4" |
| Turning Radius-Outside | 6.35m | 20'10" | 7.15m | 23'5" | 7.15m | 23'5" | 7m | 23' |
| Max. Slope | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 5°/5° | 4.5°/4.5° | 4.5°/4.5° |
| Tire Type | Solid | | Foam-filled | | Foam-filled | | Foam-filled | |
| Tire Models | 36x14-20 | | 15-625 | | 15-625 | | 385/45-28 | |
| Ground Pressure, Tyres | 695.2 kPa | 100.8 psi | 754.6 kPa | 109.5 psi | 818.4 kPa | 118.7 psi | 968 kPa | 140.4 psi |
| POWER | | | | | | | | |
| Lithium Battery | 80V 228Ah | | 80V 304Ah | | 80V 375Ah | | 80V 460Ah | |
| HYDRAULIC SYSTEM | | | | | | | | |
| Hydraulic Oil Volume | 90L | 23.8gal | 115L | 30.4gal | 115L | 30.4gal | 140L | 37gal |
| WEIGHT | | | | | | | | |
| Machine Weight | 10,800kg | 23,810 lbs | 15,200kg | 33,510 lbs | 16,500kg | 36,376 lbs | 19,500kg | 42,990 lbs |