

HERCULES

25mm Manual Swing Type Fire Hose Reel



Information

The Hercules 25mm x 30m Fire Hose Reel is approved for use in Singapore, complying with the requirements of Singapore Standard 575 : 2012.

With double 180 rotating hinge, it allows for maximum movement of the fire hose reel without restricting fire fighting ability.

Installation

In accordance to Singapore Fire Code, Fire Hose Reels shall be sited within 5m from the exit door but not inside the staircase. They can cover an area up to 36m in radius. Fire hose reels located in a room cannot cover areas outside of the room.

Compliance



EN694



SG Fire Code



Singapore

Fully compliant to Singapore Fire Code.

Meticulously tested in Singapore.

Fire Class



Class A

Usage



Turn



Run out



Aim

1. Turn on on/off water supply before running out hose.
2. Run out with the hose.
3. Aim at base of fire and rotate nozzle to discharge water.

Before attempting to fight a fire, always ensure that you have an escape route. Fire fighting is a high risk activity, when in doubt, always choose to escape.

FIRE HOSE REEL - SWING TYPE	
Model	HRL-HERC01
Standard	EN 671 - 1 : 2012
Hose Diameter	25mm
Hose Length	30M
Discharge Distance	> 6m
Max working pressure	1.2MPA
Plate Material	Steel
Nozzle	Steel
Weight	22.75KG
Pack Dimension(mm)	600x600x290
PART NO	HRL-HERC01



Dual 180 rotation hinges.