



**SPOTCOOLER / PORTABLE AIR-CONDITIONER**

| Description                    | Model   |   |
|--------------------------------|---|---|
|                                | HPC-6000  | HPC-8000  |
| <b>Cooling Capacity</b>        | 6.8kW / 23,200BTU / 1.9RT                         | 9.2kW / 31,600BTU / 2.6RT                         |
| <b>Rated Current</b>           | 12.5A   | 16.5A   |
| <b>Electrical Requirements</b> | 1PH/230V/50Hz                                     |   |
| <b>Power Consumption</b>       | 2.5kW   | 3.3kW   |
| <b>Industrial Power Plug</b>   | 16A 2P+E  |   |
| <b>Air Volume</b>              | 1,500m <sup>3</sup> /hr                           | 1,700m <sup>3</sup> /hr                           |
| <b>Air Duct</b>                | Cold: 2 nos. 0.5m length<br>Hot: 1 nos. 6m length | Cold: 3 nos. 0.5m length<br>Hot: 1 nos. 6m length |
| <b>Compressor</b>              | Rotary  |   |
| <b>Refrigerant</b>             | R-22 / R-410A                                     |   |
| <b>Air filter</b>              | Aluminum, Vinyl chloride                          |   |
| <b>Operating Condition</b>     | 18 ~ 35°C   |   |
| <b>Condensate tank</b>         | 12L   |   |
| <b>Dimension (W x D x H)</b>   | 560 x 620 x 1280 (mm)                             | 580 x 640 x 1300 (mm)                             |
| <b>Weight</b>                  | 90kg  | 95kg  |
| <b>Max. Sound Level @ 10m</b>  | 68dB(A)   |   |

*Note: Please remove the water in the condensate tank in case alarm lamp is on due to high humidity.*