

- Diesel
- Electric
- Super Silent
- Q Pack (quiet)
- 3" Size
- Water
- Sludge
- Oil/Fuel
- Chemical
- Sewage

## HL80M / HL80M Q Pack



The Godwin Dri-Prime 3" HL80M pump is an extremely powerful yet compact pump with flow capabilities to 101 m<sup>3</sup>/hr and discharge heads to 100m. The HL80M features the unique Godwin high pressure oil bath mechanical seal design. This allows for dry running for prolonged periods while automatically priming and repriming. Able to perform in the toughest conditions, the HL80M can handle solids up to 25 mm in diameter. This makes it an extremely effective pump, suitable for both slurry and clean water applications. The powerful HL80M has proven itself a pump of choice for sewage handling, dewatering, local authority usage and many other applications.

### Accessories



✓ Strainer



✓ Fuel Tank



✓ Hoses



✓ Adaptors



✓ Drip Tray



✓ Settlement Tank



✓ Telemetry



○ Autostart Float

Maximum Operating Speed	2,400 rpm
Maximum Operating Temperature	176 °F (80 °C)
Maximum Working Pressure	P145 psi (10 Bar)
Maximum Suction Pressure	87 psi (6 Bar)
Maximum Casing Pressure	218 psi (15 Bar)
Fuel Tank Capacity	19.8 gal. (75 litres)
Fuel Consumption	19.7 gph (74.6 lph)
Pipe Connections:	Suction: 100 mm (4" BS10 table 'D')
	Discharge: 80 mm (BS EN 1,092 - 1 PN16)
Solids Handling	25 mm
Engine	PERKINS 104 - 19
Nominal Speed	1,800 rpm to 2,200 rpm
Rated Power	22 kW to 36 kW
L x W x H	1,500 mm x 1,240 mm x 1,750 mm
Operational Weight	1,034 kg

- Ideal for wellpoint jetting applications
- Water mains filling and testing
- Deep excavation dewatering
- Potable water transfer
- Standby fire pumps

