

# WSC-4000



## Features

Weltem WSC-4000 are designed for a fast installation and start up. They can be used usefully where access to the outside is difficult and some distance from internal rooms because outdoor unit (heat exchanger) can be placed up to 30 meters. They are economical units which does not need providing of the water continuously. Quiet in operation enables them to be used in general offices as well. With their durable metal construction and 4 wheels, they are very useful for rental. They are space-efficient because they don't need to have hot air exhaust duct. A control panel provides ease of use and contains a self-diagnostic function. Choice of continuous operation or automatic timer.



WSC-4000  
Figure 1

## Specifications

Model	Cooling Capacity	Refrigerant	Electrical supply	Recommended Fuse Size(MCCB)	Operating range
WSC-4000	16,665BTU (4.9Kw)	R410A (0.90kg)	230V, 1phase, 50hz	15A	18~45°C

Model	Depth/Width/Height/Weight (Indoor unit)	Depth/Width/Height/Weight (outdoor unit)	Fan speeds	Air flow (high/low)	Noise level at 3m (Indoor unit, high/low)	Control
WSC-4000	705 / 350 / 865mm / 91kg	565 / 275 / 405mm / 20kg	2	780 / 700 m <sup>3</sup> /h	56 / 52 dBA	Electronic

**NOTE:** Refrigerant and Electrical supply can be different per country. Please check the label on the unit for proper information.